

Single hole earth points



Earth points and bosses



Hole size	Length	Weight	Part no.
M8 x 15mm	80mm	0.14kg	PC100-FU
M10 x 15mm	80mm	0.14kg	PC101
M12 x 15mm	80mm	0.14kg	PC102
M16 x 15mm	80mm	0.14kg	PC103

Stem diameter = 10.7mm (70mm²)

Two hole earth points



Hole Size	Length	Weight	Part no.
M8 x 12mm	80mm	0.44kg	PC115-FU
Supplied c/w front plate for connection of 25mm x 3mm copper tape or 70mm ² stranded copper cable.			
M8 x 12mm	80mm	0.44kg	PC120
Supplied c/w front plate for connection of 25mm x 3mm copper tape or 8mm diameter solid circular copper.			
M8 x 12mm	80mm	0.28kg	PC125

Stem diameter = 10.7mm (70mm²)

Four hole earth points




Hole size	Length	Weight	Part no.
M8 x 14mm	75mm	0.41kg	PC110

Stem diameter = 10.7mm (70mm²)

Earth points and bosses

Earth points with pre-welded tails

Type	Weight each	Part no.
As PC100-FU with prewelded 500m long tail of 70mm sq PVC insulated earth cable	0.56kg	PC105
As PC101 with prewelded 500m long tail of 70mm sq PVC insulated earth cable	0.56kg	PC106
As PC102 with prewelded 500m long tail of 70mm sq PVC insulated earth cable	0.56kg	PC107
As PC103 with prewelded 500m long tail of 70mm sq PVC insulated earth cable	0.56kg	PC108
As PC110 with prewelded 500m long tail of 70mm sq PVC insulated earth cable	1.14kg	PC111
As PC115-FU with prewelded 500m long tail of 70mm sq PVC insulated earth cable	0.84kg	PC116
As PC120 with prewelded 500m long tail of 70mm sq PVC insulated earth cable	0.84kg	PC121
As PC125 with prewelded 500m long tail of 70mm sq PVC insulated earth cable	0.84kg	PC126-FU



Earth boss

Length	Diameter	Thread size	Weight each	Part no.
50mm	50mm	M10	0.79kg	EB001

Made of mild steel to BS970 230M07 (ENIA) with phosphor bronze stud and nuts. For welding to steel vessels/tanks/structures. Wrap connections with Denso tape.

