


## Earth rod clamps

### Rod to tape clamp (type A)


Nominal rod diameter	Max. conductor	Weight each	Part no.
1/2" 12.7mm	26 x 12mm	0.15kg	<b>CR105</b>
5/8" 16mm	26 x 12mm	0.15kg	<b>CR105</b>
3/4" 20mm	26 x 10mm	0.15kg	<b>CR105</b>
5/8" 16mm	30 x 2mm	0.16kg	<b>CR108</b>
3/4" 20mm	30 x 2mm	0.16kg	<b>CR108</b>
5/8" 16mm	40 x 12mm	0.24kg	<b>CR110</b>
5/8" 16mm	51 x 8mm	0.30kg	<b>CR115</b>
3/4" 20mm	51 x 12mm	0.30kg	<b>CR125</b>
1/2" 12.7mm	26 x 20mm	0.23kg	<b>CR130</b>
5/8" 16mm	26 x 18mm	0.23kg	<b>CR130</b>
3/4" 20mm	26 x 10mm	0.23kg	<b>CR130</b>
1" 25mm	26 x 10mm	0.23kg	<b>CR130</b>



All Furse earth rod clamps have high strength copper alloy bodies and screws e.g. aluminium bronze, phosphor bronze etc., COMMERCIAL BRASS IS NOT USED. Corrosion resistance, conductivity and mechanical strength are essential considerations in clamp design to ensure an earthing system remains operative for many years.

### Rod to cable clamp (type G)


Nominal rod diameter	Conductor range	Weight each	Part no.
3/8" 9.5mm	6-35mm <sup>2</sup>	0.03kg	<b>CR505</b>
1/2" 12.5mm	16-50mm <sup>2</sup>	0.05kg	<b>CR510-FU*</b>
5/8" 16mm	16-70mm <sup>2</sup>	0.06kg	<b>CR515*</b>
3/4" 20mm	35-95mm <sup>2</sup>	0.06kg	<b>CR520*</b>
1" 25mm	70-120mm <sup>2</sup>	0.14kg	<b>CR525</b>




\* Suitable for use with 8mm Ø solid circular copper conductor.

### 'U' bolt rod clamp (type E)


Nominal rod diameter	Hole centres	Tape width	Weight each	Part no.
5/8"	37mm	-	0.20kg	<b>CR305</b>
3/4"	37mm	-	0.20kg	<b>CR310</b>
1"	37mm	-	0.20kg	<b>CR315</b>
5/8"	37mm	25mm	0.26kg	<b>CR320</b>
1" - 1 1/2"	54mm	-	0.37kg	<b>CR325</b>
1 1/2" - 2"	64mm	-	0.44kg	<b>CR330</b>



'U' Bolt threaded M10. CR320 includes additional plate to allow tape to be clamped without drilling.



## Rod to cable clamp (type GUV)




## Earth rod clamps

Nominal rod diameter	Conductor range	Weight each	Part no.
5/8" 16mm	16-95mm <sup>2</sup>	0.39kg	<b>CR700*</b>
3/4" 20mm	16-70mm <sup>2</sup>	0.39kg	<b>CR700*</b>
5/8" 16mm	70-185mm <sup>2</sup>	0.39kg	<b>CR705</b>
3/4" 20mm	70-150mm <sup>2</sup>	0.39kg	<b>CR705</b>
5/8" 16mm	150-300mm <sup>2</sup>	0.62kg	<b>CR730</b>
3/4" 20mm	150-300mm <sup>2</sup>	0.62kg	<b>CR730</b>

\* Suitable for use with 8mm Ø solid circular copper conductor.

## Rod to cable lug clamp (type B)



Nominal rod diameter	Rod type	Weight each	Part no.
3/8" 9.5mm	Copperbond	0.09kg	<b>CR205</b>
5/8" 16mm	Copperbond	0.30kg	<b>CR215</b>
5/8" 15mm	Solid copper	0.30kg	<b>CR220</b>
3/4" 20mm	Copperbond	0.30kg	<b>CR225</b>
3/4" 20mm	Solid copper	0.30kg	<b>CR230</b>