PROPAK-SIGMA

HIGH PERFORMANCE, RUGGED DEPENDABILITY, TRUSTED TECHNOLOGY



The ProPak-Sigma has been designed specifically for use as a compliance set in Marine or Industrial fire fighting environments.

The entire ProPak range has been approved to EN137:2006 Type 2, incorporating the stringent Full Flame Engulfment Test, and to the 9th amendment of the MED meaning that it has the latest approval for the Marine market.

PRODUCT HIGHLIGHTS

- EN137:2006 Type 2 MED Approved Breathing Apparatus
- Compliance set for Marine and Industrial firefighting environments
- Rigid backframe construction
- Easily removable pneumatics
- Simple to service and maintain



PROPAK-SIGMA

SELF CONTAINED BREATHING APPARATUS



MAJOR COMPONENTS

Compact positive pressure demand valve featuring servo-assisted, tilting diaphragm mechanism with low inspiratory resistance and responsive dynamic performance, automatic first breath actuation and hands free bypass facility

REDUCING VALVE

First stage pressure reducing valve featuring non-adjustable, spring loaded piston mechanism and outlet supply protected by pressure relief valve

HOSES

Stainless steel swivel hose fittings Medium pressure hose High pressure hose Medium working pressure 16 bar Minimum burst pressure 80 bar Maximum working pressure 450 bar Minimum burst pressure 800 bar

PRESSURE INDICATOR & WARNING WHISTLE

Bourdon tube type dial indicator Heat and Impact resistant polycarbonate lens

COMMUNICATIONS

The Sabrecom2 is a radio communication interface designed for use with Scott Safety's range of positive pressure full facemasks. Fully integrated and ready to use the Sabrecom 2 is approved to EN136 class 3, meeting the stringent flame and radiant heat test requirements.

OPTIONS

The Scott Safety ProPak-Sigma can be specified in many configurations including Duo, Split Demand Valve Coupling (SDC), Y Piece (Y2C) and attachments for Airline, which can be used for Rescue Second Man and Decontamination.

Product Specifications	
Weight	
Single Configuration (less cylinder)	2.6kg
Single Configuration and facemask (less cylinder)	3.2kg
Dimensions	
Length	630mm
Width	285mm
Depth (with a 6 litre 200 bar cylinder)	215mm

Ordering Information		
Part Number	Description	Application
ProPak-Sigma	EN137 Approved, Type 2	Marine / Industrial Fire Fighting













Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.

::: UK Office Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399 Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.