

4510

Bench Conductivity/TDS Meter

The 4510 is easy to use but with the flexibility to meet the broadest range of applications and for those where greater accuracy is required the 4510 has automatic conductivity standard recognition and endpoint detection. Set-up options include cell constant, temperature coefficient and reference temperature. The instrument can store up to 32 readings, which can also be sent to a printer or transferred to computer via DataWay and the RS232 interface.

Technical Specification

Conductivity

Range	6 auto-selected from 0 to 19999mS*
Resolution	0.01µS to 1mS
Accuracy	±0.5% ±2 digits
Automatic std. recognition	10µS, 84µS, 1413µS, 12.88mS
Cell constant	0.010 to 19.999

TDS

Range	6 auto-select from 0-19999g/l*
Resolution	0.01mg/l to 1g/l
Accuracy	±0.5% ±2 digits
EC Ratio	0.50 to 0.80

Temperature

Range	-10 to 105°C
Resolution	0.1°C
Accuracy	±0.5°C
ATC and manual	0 to 100°C
Temperature coefficient	0.00% to 4.00%/°C
Reference temperature	18, 20 or 25°C
Outputs	Analogue and RS232
Connector	7-pin DIN
Power	9V AC ±10% @ 50/60Hz**
Size (l x w x d), mm	210 x 250 x 55
Weight, g	850

Key Features

- Simultaneous display of conductivity or TDS and temperature
- Automatic selection of range for best resolution
- Calibration by cell constant or standard solutions
- Automatic standard recognition
- Storage of up to 32 results
- Bi-directional RS232 link to printer or PC



4510

Part code: 451 001

Ordering Information

Part Code	Description
451 001	4510 conductivity meter supplied with glass conductivity probe with ATC (K=1) (027 013), electrode holder (903 300) and UK power supply (021 030)

*With K=10 cell

** Voltage variants available see page 94





Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.