

## KB 23 (E3.1) - Refrigerated microbiological incubator with program controller

The KB is the all-rounder for microorganisms. With its wide range of individual programming functions, including a real-time clock function and an enormous temperature span, it can be used for a broad range of sophisticated applications in laboratories – with minimal dehumidification of specimens and impressive extra performance. The APT.line™ with its electronically controlled preheating chamber ensures rapid recovery times and maximum precision, unaffected by the ambient temperature.



### ▶ Performance features and equipment :

- Electronically controlled APT.line™ preheating chamber and patented DCT™ refrigeration system assuring temperature accuracy and reproducible results in both heating and cooling situations
- Temperature range: temperature range 0 °C to 100 °C (32 °F to 212 °F) (at ambient temperature ≤ 20 °C (68 °F))
- MP controller with 2 programs with 10 sections each, alternatively switchable to 1 program with 20 sections
  - Integrated week program timer with real time function
  - Adjustable ramp function via program editor
  - Integrated week program timer with real time function
- Digital temperature setting with an accuracy of a tenth of a degree
- Adjustable fan speed
- Elapsed time indicator
- Independent adjustable temperature safety device, Class 3.1 (DIN 12880) with visual and acoustic alarm
- Inner glass door
- Environmentally friendly refrigerant R 134a
- RS 422 interface for communication software APT-COM™ DataControlSystem, or switch over to printer output with RS 232 / RS 422 interface converter
- Adjustable intervals for printer
- Units up to 115 liters (4.1 cu.ft) are stackable
- 2 stainless steel racks
- BINDER test certificate



KB 23 (E3.1)

<b>Exterior dimensions</b>	
Width (mm/inch)	433 / 17.1
Height (inclusive feet) (mm/inch)	618 / 24.3
Depth (mm/inch)	516 / 20.3
Plus door handle, l-panel, connection (mm/inch)	73 / 2.9
Wall clearance (mm/inch)	100 / 3.9
Wall clearance with open door(s) (mm/inch)	100 / 3.9
Steam space volume (l/cu.ft.)	36 / 1.3
Number of doors	1
Number of inner glass doors	1
<b>Interior dimensions</b>	
Width (mm/inch)	222 / 8.7
Height (mm/inch)	330 / 13.0
Depth (mm/inch)	277 / 10.9
<b>Interior volume (l/cu.ft.)</b>	
Racks (number standard/max.)	2 / 3
Load per rack (kg/lbs.)	10 / 22
Permitted total load (kg/lbs.)	25 / 55
Weight (empty) (kg/lbs.)	44 / 97
<b>Temperature data</b>	
Temperature range (°C/°F) 1)	0 - 100 / 32-212
Temperature variation	
at 5 °C (9 °F) (± °C)	0.7
at 25 °C (45 °F) (± °C)	0.3
at 40 °C (72 °F) (± °C)	0.3
Temperature fluctuation	
at 5 °C (9 °F) (± °C) (± °C)	0.2
at 40 °C (72 °F) (± °C)	0.2
Heating up time 1) to 40 °C (72 °F) (Min.)	11
Cooling down time from 40 °C (72 °F) to 5 °C (9 °F) (Min.)2)	61
Recovery time after door was open for 30 sec 1)	
at 5 °C (9 °F) (Min.)	5
at 40 °C (72 °F) (Min.)	2
<b>Electrical data</b>	
Housing protection acc. to EN 60529	IP 20
Nominal voltage (±10 %) 50 / 60 Hz (V)	230
Nominal power (kW)	0.34
Energy consumption 3)	
at 5 °C (9 °F) (W)	50
at 40 °C (72 °F) (W)	60


Based on the ice increase on the evaporators the refrigerating capacity decreases at a set value of < 0 °C (32 °F). For this reason the chambers have to be defrosted regularly (approx. once a week).

1) at an ambient temperature ≤20 °C (68 °F)

2) up to 98 % of the set value

3) these values can be used upon calculation of air conditioning systems

All technical data are specified for units with standard equipment at an ambient temperature of 25 °C and a voltage fluctuation of ±10 %. The temperature data are determined in accordance to factory standard following DIN 12880 respecting the recommended wall clearances of 10 % of the height, width and depth of the inner chamber. All indications are average values, typical for units produced in series. We reserve the right to alter technical specifications at all times.




## ▶ Access ports

With silicon plugs for inserting external measuring devices into the chamber. Access ports with 10, 30, 50, 100 mm (0.4, 1.2, 2, 3.94 inch) diameter.



## ▶ Calibration certificates and validation

BINDER can significantly reduce the time and effort needed for equipment qualification and validation. We draw on unparalleled knowledge of our equipment applications and years of experience in certification.



## ▶ Operational data documentation: APT-COM™ DataControlSystem

The only standard software that guarantees seamless documentation of all testing parameters in compliance with standards. Can be fully validated in accordance with GLP/GMP and FDA 21 CFR Part 11.

**KB 23 (E3.1)**

Access port with silicone plugs, 10 mm (0.39 inch), 30 mm (1.18 inch), 50 mm (1.97 inch), 100 mm (3.94 inch)	<input type="radio"/>
Extension to factory calibration certificate. Each additional measurement at an additional measuring point or temperature	<input type="radio"/>
Temperature measurement acc. to DIN 12880 (27 measuring points) at 37 °C (98.6 °F) or at specified temperature with measuring protocol and certificate	<input type="radio"/>
Factory calibration certificate. Measurement in center of chamber at 37 °C (98.6 °F) or at specified testing temperature	<input type="radio"/>
Securing elements for additional fastening of racks (1 set of 4)	<input type="radio"/>
Rack, stainless steel	<input type="radio"/>
Shelf, perforated, stainless steel	<input type="radio"/>
Lockable door	<input type="radio"/>



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



**UK Office**

**Keison Products,**

**P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.**

**Tel: +44 (0)1245 600560**

**Fax: +44 (0)1245 600030**

**Email: [sales@keison.co.uk](mailto:sales@keison.co.uk)**

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.