

4-gas detector with pump

H₂S
CO
O₂
LEL

GasAlert MaxXT



WATER RESISTANT 

Simple operation with pump



The rugged GasAlertMax XT reliably monitors for up to four gas hazards and combines straightforward one-button field operation with an integrated sampling pump. Tamper-proof, user-adjustable options enable the instrument to be customized to suit your application. Confined space entry and remote sampling have never been so easy with new, intelligent SmartSample pump technology. Minimize pump blockages and improve remote sampling result accuracy. Powered by a rechargeable battery pack that provides runtime for an entire 13 hour shift, the compact GasAlertMax XT comes with standard event logging and datalogging. The GasAlertMax XT is fully compatible with the MicroDock II automated test and calibration system.



Standard Package Contents

- Detector complete with specified sensor(s), stainless steel alligator clip and concussion-proof housing
- Rechargeable lithium polymer battery
- Charging adaptor
- 3 ft./1 m calibration hose with quick connect
- 10 ft./3 m sampling hose with particulate filter and quick connect
- Reversible screwdriver
- Kit of 5 spare pump filter
- Manual
- Multi-language manual CD

General Specifications

Size	5.1 x 2.8 x 2.0 in. / 13.1 x 7.0 x 5.2 cm
Weight	11.1 oz. / 316 g
Typical battery life	13 hours @ 32°F / 0°C 10 hours @ -4°F / -20°C Recharges in 6 hours
Certifications and approvals	<p> Class I, Div. 1, Gr. A, B, C, D</p> <p>ATEX:  II 1 G Ga Ex ia IIC T4</p> <p>IECEX: Ga Ex ia IIC T4</p> <p>INMETRO: BR-Ex ia IIC T4</p> <p>CE: European Conformity</p>
Warranty	Full 2-year warranty including all sensors

BW
Technologies
by Honeywell

GasAlertMax XT 4-Gas Detector	Order Number	
	Yellow	Black
%LEL, O ₂ , H ₂ S, CO	XT-XWHM-Y-NA	XT-XWHM-B-NA

GasAlertMax XT 3-Gas Detector	Order Number	
	Yellow	Black
%LEL, O ₂ , H ₂ S	XT-XWH0-Y-NA	XT-XWH0-B-NA
%LEL, O ₂ , CO	XT-XW0M-Y-NA	XT-XW0M-B-NA
O ₂ , H ₂ S, CO	XT-X0HM-Y-NA	XT-X0HM-B-NA
%LEL, H ₂ S, CO	XT-0WHM-Y-NA	XT-0WHM-B-NA

GasAlertMax XT 2-Gas Detector	Order Number	
	Yellow	Black
%LEL, O ₂	XT-XW00-Y-NA	XT-XW00-B-NA
H ₂ S, CO	XT-00HM-Y-NA	XT-00HM-B-NA
O ₂ , H ₂ S	XT-X0H0-Y-NA	XT-X0H0-B-NA
O ₂ , CO	XT-X00M-Y-NA	XT-X00M-B-NA
%LEL, H ₂ S	XT-0WH0-Y-NA	XT-0WH0-B-NA
%LEL, CO	XT-0W0M-Y-NA	XT-0W0M-B-NA

GasAlertMax XT 1-Gas Detector	Order Number	
	Yellow	Black
O ₂	XT-X000-Y-NA	XT-X000-B-NA
%LEL	XT-0W00-Y-NA	XT-0W00-B-NA
H ₂ S	XT-00H0-Y-NA	XT-00H0-B-NA
CO	XT-000M-Y-NA	XT-000M-B-NA

GasAlertMax XT Region Codes

For orders outside North America, change order number suffix “-NA” to:

“-EU”	Europe	“-BR”	Brazil
“-UK”	United Kingdom	“-OR”	Other region with 3-pin UK plug
“-AU”	Australia	“-OE”	Other region with 2-pin UK plug
“-CN”	China/New Zealand		



MicroDock II

Automatic test and calibration station
(see MicroDock II section for additional information)

Gas Legend

%LEL	Combustible
O ₂	Oxygen
H ₂ S	Hydrogen sulfide
CO	Carbon monoxide

Confined Space Kit

GasAlertMax XT deluxe confined space kit *Detector and calibration gas sold separately*
 Carrying case for **GasAlertMax XT** with foam insert

Order Number

XT-CK-DL
 XT-CK-CC

Carrying Accessories

Concussion-proof boot with stainless steel alligator-style clip
 Carrying holster for detector and sampling hose
 Neck strap with safety release
 Extension strap (4 ft./1.2 m)
 Short strap (6 in./15.2 cm)
 Armband
 Chest harness

Order Number

GA-BXT
 GA-HXT
 GA-NS-1
 GA-ES-1
 GA-LY-1
 GA-ARM-1
 GA-CH-2

Power Options and Spares

Multi-unit (5) cradle charger
 Multi-unit power adaptor
 12-24 V_{DC} vehicle power adaptor
 12-24 V_{DC} direct-wire power adaptor
 Replacement power adaptor

Order Number

XT-C01-MC5
 GA-PA-1-MC5*
 GA-VPA-1
 GA-PA-3
 GA-PA-1-NA**

*For regions outside North America add to the end of the order number: "-EU" for Europe, "-UK" for United Kingdom and "-AU" for Australia/China.
 **For regions outside North America replace "-NA" with: "-EU" for Europe, "-UK" for United Kingdom and "-AU" for Australia/China.

Deluxe Confined Space Kit
 XT-CK-DL
Order detector and calibration gas separately



Multi-Unit Cradle Charger
 XT-C01-MC5
Simultaneously charge 5 detectors



Multi-Unit Power Adaptor
 GA-PA-1-MC5
Simultaneously charge 5 detectors



Vehicle Power Adaptor
 12-24 V_{DC}
 GA-VPA-1



Direct-Wire Power Adaptor
 12-24 V_{DC}
 GA-PA-3
Used for emergency vehicles and other applications



Concussion-Proof Boot
 GA-BXT



Carrying Holster
 GA-HXT
Sampling Probe
 GA-PROB1-1

Datalogging Accessories

	Order Number
IR connectivity kit with Fleet Manager II software	GA-USB1-IR

Sampling/Testing Equipment and Spares

	Order Number
MicroDock II automatic test and calibration system—	
- base station and GasAlertMax XT docking module with charging cable	DOCK2-2-1C1M-00-N*
- base station and GasAlertMax XT docking module without charging cable	DOCK2-2-1M-00-N*
- GasAlertMax XT docking module with charging cable	DOCK2-0-1C1M-00-N
- GasAlertMax XT docking module without charging cable	DOCK2-0-1M-00-N
<i>For complete MicroDock II system configuration information, see MicroDock II section.</i>	
Quick connect fitting spares for hoses, kit of 2	M0931K
Auxiliary filter for GasAlertMax XT pump, kit of 5	M5-AF-K2
Auxiliary filter for GasAlertMax XT pump, kit of 100	M5-AF-K2-100
Hydrophobic pump filter replacement, kit of 5	XT-RF-H5
Hydrophobic pump filter replacement, kit of 50	XT-RF-H50
Hydrophobic pump filter replacement, kit of 100	XT-RF-H100
Particulate pump filter replacement, kit of 5	GA-PFMAX
Particulate pump filter replacement, kit of 50	GA-PFMAX-50
Particulate pump filter replacement, kit of 100	GA-PFMAX-100

* Change order number suffix “-N” to: “-E” for European versions, “-U” for United Kingdom versions, “-A” for Australian versions.

Sensor Spares and Replacements


	Order Number
Quad sensor screen filters, kit of 2	XT-SS
Quad sensor screen filters, kit of 10	XT-SS-K1
Replacement MICROpeL combustibile (LEL) sensor	SR-W-MP75C
Replacement MICROceL oxygen (O ₂) sensor	SR-X-MC
Replacement MICROceL hydrogen sulfide (H ₂ S) sensor	SR-H-MC
Replacement MICROceL carbon monoxide (CO) sensor	SR-M-MC
Dummy sensor for combustibile sensor location	SR-W-MC-DUM
Dummy sensor for oxygen sensor location	SR-X-MC-DUM
Dummy sensor for toxic sensor locations	SR-TOX-MC-DUM



IR Connectivity Kit
GA-USB1-IR
Use for data download and instrument set-up options



Auxiliary Pump Filter
M5-AF-K2 / M5-AF-K100
For high dust environments;
available in kits of 5 or 100



Quick Connect Fitting
M0931K
Quick connect fitting for hoses, kit of 2

Hydrophobic Pump Filter
XT-RF-H5 / XT-RF-H50 / XT-RF-H100
Particulate Pump Filter
GA-PFMAX / GA-PFMAX-50 / GAPFMAX-100
Both are available in kits of 5, 50 or 100

