

TLD Rapid Cooling High Temperature Ovens

Standard features

- ✓ 400°C maximum operating temperature.
- ✓ 3508P1 Programmable controller providing automatic activation of the cooling blower.
- ✓ Overtemperature protection with digital set & display.
- ✓ Horizontal forced air circulation from rear mounted fan.
- ✓ Excellent performance & reliability.
- ✓ Door locks easily operated whilst wearing gloves.
- ✓ Stainless steel liner.
- ✓ Steel section construction.
- ✓ Stainless steel mesh shelves.



TLD/3

Ideal for applications such as tempering, glass annealing, preheating and stress relieving these small scale industrial ovens are able to operate efficiently up to 400°C.

These ovens are frequently used for annealing thermo-luminescent dosimeters.

Options

specify these at time of order

- ✦ Independent over-temperature protection with digital set & display.
- ✦ Digital process timer.
- ✦ Programmable controller.
- ✦ Additional shelves.
- ✦ Stoving & curing kit to extract volatile fumes.
- ✦ Chart recorders & paper free digital acquisition (DAQ) devices (externally mounted for the TLD/3).

Model	Max temp (°C)	Temp stability (°C)	Temp uniformity (°C)	Heat-up time to max (mins)	Heating/cooling rate (°C/min) [†]	Dimensions		Shelves fitted/accepted	Shelves loading Each/total (kg)	Volume (litres)	W't (kg)	Max power (W)	Power supply
						Internal H x W x D (mm)	External H x W x D (mm)						
TLD/3	400	±1	±5.0	60	4	150 x 150 x 100	530 x 370 x 500	2 / 2	—	28	26	1000	Single phase
TLD/28	400	±1	±5.0	60	8	305 x 305 x 305	880 x 675 x 885	3 / 4	10 20	28	62	1000	Single phase



Minimum operating temperature 50°C.

Uniformity values are measured in an empty chamber with vents closed after a period of stabilisation.

Shelf loadings are based on evenly distributed weight.

[†] Based upon cooling an empty chamber



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.