

Ashing Furnace AAF - 3 & 7 litres

General Information

The AAF ashing furnace range is designed specifically to provide optimum ashing conditions to ensure complete combustion of the sample.

The AAF 11/3 & AAF 11/7 ashing furnaces provide a continuous flow of preheated air through the chamber, and are designed to comply with ISO 1171:2010, ASTM D3174-04: 2010 and ASTM D4422.

Standard features

- 1100 °C maximum operating temperatures
- Carbolite Gero 301 controller, with single ramp to set-point & process timer
- Large floor area allows for large numbers of samples
- Ideal for ashing foods, plastics, coal & other hydrocarbon materials
- Designed to comply with ISO 1171:2010, ASTM D3174-04:2010 and ASTM D4422
- Wire elements are protected from chemical & mechanical damage by a hard wearing alumina based liner
- 4 sided heating (2 sides, roof & hearth)
- Air inlet & tall chimney give airflow of 4 to 5 changes per minute
- Low chamber height holds airflow close to samples for optimum combustion
- Powerful elements with graded winding compensate for heat loss due to high airflow
- Preheating of air before it enters the chamber gives excellent uniformity
- Sample tray and loading handle

Options (specify these at time of order)

- 2 phase electrical supply for AAF 11/7
- Over-temperature protection (recommended to protect valuable contents & for unattended operation)
- A range of sophisticated digital controllers, multi-segment programmers and data loggers is available. These can be fitted with RS232, RS485 or Ethernet communications

Technical Specifications



Ashing Furnace AAF - 3 & 7 litres

AAF 11/3

Max temp (°C)	1100
Heat-up time (mins)	155
Max continuous operating temp (°C)	1000
Dimensions: Internal H x W x D (mm)	90 x 150 x 250
Dimensions: External H x W x D (mm)	585 x 375 x 485
Dimensions: External with door open H x W x D (mm)	800 x 375 x 485
Dimensions: Height to top chimney (mm)	780
Volume (litres)	3
Max power (W)	2100
Holding power (W)	1270
Thermocouple type	K
Weight (kg)	22

AAF 11/7

Max temp (°C)	1100
Heat-up time (mins)	155
Max continuous operating temp (°C)	1000
Dimensions: Internal H x W x D (mm)	90 x 170 x 455
Dimensions: External H x W x D (mm)	650 x 430 x 740
Dimensions: External with door open H x W x D (mm)	905 x 430 x 740
Dimensions: Height to top chimney (mm)	1060
Volume (litres)	7
Max power (W)	4000
Holding power (W)	2624
Thermocouple type	K
Weight (kg)	63

Please note:

- Holding power is measured at 500°C
- Heat up rate is measured to 100°C below max, using an empty chamber
- Maximum power and heat up times based on a 240V supply



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.