

Laboratory Oven - AX

General Information

The Apex AX range of 250°C laboratory ovens comprises three bench-top sized models equipped with the R38 digital PID temperature controller.



Standard features

- 250°C maximum operating temperature
- 30, 60 or 120 litres chamber volumes
- Equipped with the R38 digital PID temperature controller
- Fan convection for rapid heating & excellent uniformity
- Chemically resistant stainless steel liner
- Two adjustable nickel-chrome plated wire shelves
- Lever latch door & airtight silicone seal
- Compliant with safety standard BS EN 61010-2-010:2003

Options (specify these at time of order)

- Over-temperature protection (recommended to protect valuable contents & for unattended operation)
- Digital countdown timer to switch oven off
- Additional sets of shelves & runners
- Lockable door
- Low voltage options for use below 220 V
- Routine spares kit

Technical Specifications

AX30

Max temp (°C)	250
Min temp (°C)	Ambient +30
Temp uniformity (°C)	±5.0 @ 250°C
Heat-up time (mins)	23
Recovery time (mins)	3
Dimensions: Internal H x W x D (mm)	295 x 300 x 320
Dimensions: External H x W x D (mm)	440 x 590 x 465
Shelves fitted / accepted	2 / 4
Shelf loading each / total (kg)	10 / 20
Volume (litres)	28
Air changes / hr	65
Max power (W)	1000
Holding power (W)	342
Weight (kg)	24

Laboratory Oven - AX

AX60

Max temp (°C)	250
Min temp (°C)	Ambient +30
Temp uniformity (°C)	±5.0 @ 250°C
Heat-up time (mins)	25
Recovery time (mins)	3
Dimensions: Internal H x W x D (mm)	395 x 400 x 420
Dimensions: External H x W x D (mm)	540 x 690 x 565
Shelves fitted / accepted	2 / 6
Shelf loading each / total (kg)	10 / 30
Volume (litres)	66
Air changes / hr	28
Max power (W)	1500
Holding power (W)	465
Weight (kg)	37

AX120

Max temp (°C)	250
Min temp (°C)	Ambient +30
Temp uniformity (°C)	±5.0 @ 250
Heat-up time (mins)	26
Recovery time (mins)	3
Dimensions: Internal H x W x D (mm)	495 x 500 x 520
Dimensions: External H x W x D (mm)	640 x 790 x 665
Shelves fitted / accepted	2 / 8
Shelf loading each / total (kg)	10 / 40
Volume (litres)	128
Air changes / hr	14
Max power (W)	2000
Holding power (W)	622
Weight (kg)	55

Please note:

- Uniformity is measured in an empty chamber with vents closed, after a stabilisation period
- Shelf loadings are based on evenly distributed weight
- Maximum power and heat up times based on a 240V supply
- The uniform volume is smaller than the total chamber volume
- Minimum operating temperature is ambient +30°C



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.