



## CFM : Sulphur & chlorine in coal and coke



### Combustion tube furnaces

For sulphur and chlorine tests, in accordance with BS1016 parts 6 & 7; ASTM D 3177-75; ISO 351 & 609.

Also ideal for a wide range of laboratory tube analysis applications. AUX models include an auxiliary heater for carbon and hydrogen contents tests.

### Specification

Model	Maximum temperature (°C)	Power (kW)	Heated length (mm)	Bore (mm)*
CFM 12/1	1200	1	300	1 x 38
CFM 12/2	1200	1	300	2 x 38
CFM 14/1	1400	2.8	180	1 x 38
CFM 14/2	1400	2.8	180	2 x 38
CFM 14/4	1400	3.7	180	4 x 38
CFM 14/1 (Aux)	1400	3.0	180	1 x 38
CFM 14/2 (Aux)	1400	3.0	180	2 x 38

\* - to accept 25mm bore work tubes



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



**UK Office**

**Keison Products,**

**P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.**

**Tel: +44 (0)1245 600560**

**Fax: +44 (0)1245 600030**

**Email: [sales@keison.co.uk](mailto:sales@keison.co.uk)**

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.