



Technical specification information for Carbolite CR range of 250°C clean room ovens

Model	Maximum temperature (°C)	Chamber dimensions (mm – h x w x d)	External dimensions (mm – h x w x d)	Volume (litres)	Power (kW)	Temperature stability (°C)	Temperature variation @ 250°C (°C)
CR 30	250	310/310/310	655/460/625	30	1	0.2	± 3
CR 70	250	310/470/470	655/620/790	70	1.5	0.2	± 3
CR 130	250	550/470/470	895/620/790	130	2.0	0.2	± 4
CR 180	250	820/470/470	895/620/790	180	2.5	0.2	± 5
CR 220	250	610/610/610	1115/620/790	220	3.0	0.2	± 5
CR 330	250	915/610/610	1440/780/850	330	4.5	0.2	± 5
CR 450	250	1220/610/610	1750/780/850	450	6.0	0.3	± 5
CR 670	250	1220/915/610	1750/1065/850	670	9.0	0.3	± 5
CR 840	250	1525/915/610	2050/1065/850	840	12.0	0.3	± 5
CR 900	250	1220/1220/610	1750/1420/850	900	12.0	0.3	± 5
CR 1120	250	1525/1220/610	2050/1420/850	1120	15.0	0.3	± 5
CR 1790	250	1220/1220/1220	1750/1420/1450	1790	18.0	0.3	± 5



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)1245 600560

Fax: +44 (0)1245 600030

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.