

Technical specification information for Carbolite HTF range of furnaces

Model	HTF 17/5	HTF 17/10	HTF 18/4	HTF 18/8
Maximum operating temperature (°C)	1700	1700	1800	1800
Maximum continuous operating temperature (°C)	1600	1600	1700	1700
Chamber dimensions (mm – h x w x d)	158 x 150 x 225	232 x 200 x 225	140 x 140 x 190	210 x 190 x 190
External dimensions (mm – h x w x d) with door closed with door open height to top of chimney	565 x 830 x 650 870 x 830 x 650 665			
Volume (l)	5.3	10.4	3.7	7.6
Maximum furnace load (kg)	2.5	5.0	2.1	4.2
Weight (kg)	87	106	98	114
Heat up time (minutes to 100°C below maximum temperature)	50	44	65	56
Power rating @ 230V single phase 50/60Hz (W)	4190	5920	4650	6200
Temperature stability (chimney open)	Better than $\pm 0.5^{\circ}\text{C}$ (instrument resolution)			
Holding power (W) @ 1000°C 1200°C 1400°C 1600°C 1700°C 1800°C	1290 1672 2105 2667 2985 --	1589 2043 2567 3243 3683 --	1204 1526 1942 2460 2772 3108	1524 1901 2425 3083 3453 3897
Temperature uniformity @ 1000°C 1200°C 1400°C 1600°C 1800°C	$\pm 8.5^{\circ}\text{C}$ over 90mm $\pm 7^{\circ}\text{C}$ over 100mm $\pm 5^{\circ}\text{C}$ over 120mm $\pm 4^{\circ}\text{C}$ over 130mm	$\pm 12.5^{\circ}\text{C}$ over 105mm $\pm 10^{\circ}\text{C}$ over 113mm $\pm 6.5^{\circ}\text{C}$ over 125mm $\pm 4^{\circ}\text{C}$ over 151mm	$\pm 8.5^{\circ}\text{C}$ over 113mm $\pm 7^{\circ}\text{C}$ over 129mm $\pm 5^{\circ}\text{C}$ over 109mm $\pm 4^{\circ}\text{C}$ over 113mm	$\pm 8.5^{\circ}\text{C}$ over 110mm $\pm 7^{\circ}\text{C}$ over 120mm $\pm 5^{\circ}\text{C}$ over 127mm $\pm 4^{\circ}\text{C}$ over 123mm
Voltage supplies available	208, 220, 230 & 240V single phase 50/60Hz	208, 220, 230 & 240V single phase 50/60Hz 380, 400, & 415 2-phase – 50/60Hz	208, 220, 230 & 240V single phase 50/60Hz	208, 220, 230 & 240V single phase 50/60Hz 380, 400, & 415 2-phase – 50/60Hz



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.