

Dräger REGARD HART® Control card

A multiplexing alarm card with local display, 3 common gas alarm levels, optional common fault and a remote reset input.



D-15086-2009

The Dräger REGARD HART® control card allows single or multi-drop connection to HART® intelligent gas detectors. Each card operates independently with up to nine gas detectors, or can be addressed to interface with other system cards

FEATURES AND BENEFITS

- Measuring for Ex, Tox or O₂
- Suitable for Polytron HART® transmitters only
- Up to nine HART® transmitters per card when connected in multi-drop format
- Simple operation
- Continuous display
- Password protected
- HART® digital communications and diagnostics



ST-326-2004

Dräger REGARD HART®

TECHNICAL DATA

Control card	Local alphanumeric display Front panel push buttons Front panel LED's
Inputs	2/3 wire Polytron HART® transmitters Remote reset
Outputs	A1, A 2and F/A 3 alarm relays
Power Supply	24 V DC, 100 mA
Measuring Ranges	0-1 to 0-9999
Units of Measure	vol%, ppm and many others
Gas Names	H ₂ S, CL ₂ , O ₂ , CH ₄ and many others
Approvals	Tested to EN 50270 for EMC directive, HART®

ORDER INFORMATION

Dräger REGARD HART®	42 05 900
---------------------	-----------



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.