

# Ex-Time 40

## CERTIFICATION

ATEX



Ⓜ II 2 G Ex ia IIC T4

FM



I.S. Class I Division 1 Groups A-D T4

## FEATURES & FUNCTIONS

- Quartz movement
- Robust metal casing

## Wall Clock Ex-Time 40

FOR ZONE 1

### WITH QUARTZ MOVEMENT

The intrinsically safe wall clock, Ex-Time 40, is driven by a Quartz accurate movement, powered by a LR 14 (C) type battery.

When necessary, e. g. for summer to winter time, adjustments can be quickly and simply made.

### STANDARD DELIVERY

- Ex-Time 40
- Battery
- Operating instructions
- Ex-Certificate
- EU-declaration of conformity

PROBLEM-FREE

SETTING AND ADJUSTMENT



## TECHNICAL DATA

Ambient temperature	0 °C ... +50 °C
Storage temperature	0 °C ... +50 °C
Clock Movement	Quartz
Accuracy	-5/+15 Seconds/month
Power Supply	1 x LR 14 according to IEC (type approved)
Operating time	1 year
Dimensions	400 x 60 mm
Weight	approx. 2.0 kg



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



**UK Office**

**Keison Products,**

**P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.**

**Tel: +44 (0)330 088 0560**

**Fax: +44 (0)1245 808399**

**Email: [sales@keison.co.uk](mailto:sales@keison.co.uk)**

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.