

## Electrothermal CMU Controlled Mantles



The Electrothermal CMU Controlled Mantle features aluminum housing that is tough, chemical-resistant, lightweight and easy to clean.

Available in multiple sizes and temperature ranges

- Flexible coiled heating elements absorb shock, minimizing the risk of flask breaking
- Heating element is attached to a rigid thermal insulating cartridge to ensure maximum heat transfer and support
- Heating elements and insulation form an easy-to-replace heating cartridge
- Unique air flow through ventilation slots beneath and around the rim and heating cartridge keeps the exterior "cool-to-the-touch"
- Stainless steel screen covering the heating element is grounded directly to the cable for added protection
- Mantles are double fused for added safety
- Non-skid feet and support clamps add stability

Certifications: CE, CSA



Specifications		
Material		Aluminum case stove painted
Max Element Temperature		450°C (842°F)
Cat. No.	Capacity	Electrical Requirements
CMU0050/CE	50ml	230v 50/60Hz, 75w
CMU0050/CEX1	50ml	230v 50/60Hz, 75w
CMU0050/CEX6	50ml	230v 50/60Hz, 75w EU Plug
CMU0100/CE	100ml	230v50/60Hz, 100w
CMU0100/CEX1	100ml	115v 50/60Hz, 100w
CMU0100/CEX6	100ml	230v 50/60Hz, 100w EU Plug
CMU0250/CE	250ml	230v 50/60Hz, 200w
CMU0250/CEX1	250ml	115v 50/60Hz, 200w
CMU0250/CEX6	250ml	230v 50/60Hz, 200w, EU Plug
CMU0500/CE	500ml	230v 50/60Hz, 280w
CMU0500/CEX1	500ml	115v 50/60Hz, 280w
CMU0500/CEX6	500ml	230v 50/60Hz, 280w, EU Plug
CMU1000/CE	1000ml	230v 50/60Hz 380w
CMU1000/CEX1	1000ml	115v 50/60Hz, 380w
CMU1000/CEX6	1000ml	230v 50/60Hz, 380w, EU Plug
CMU2000/CE	2000ml	230v 50/60Hz, 500w
CMU2000/CEX1	2000ml	115v 50/60Hz, 500w
CMU2000/CEX6	2000ml	230v 50/60HZ, 500w EU Plug
CMU3000/CE	3000ml	230v 50/60Hz, 500w
CMU3000/CEX1	3000ml	115v 50/60Hz, 500w
CMU3000/CEX6	3000ml	230v 50/60HZ, 500w EU Plug
CMU5000/CE	5000ml	230v 50/60Hz, 800w
CMU5000/CEX1	5000ml	115v 50/60Hz, 800w
CMU5000/CEX6	5000ml	230v 50/60Hz, 800w EU Plug

Issue 1 04/10



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.

UK Office Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560 Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.