



Anaerobic digestion

Applications

- Farm digester gas monitoring
- Food processing biogas monitoring
- Waste water biogas monitoring
- Methane recovery

Benefits

- Enables consistent collection of data for improved analysis and accurate reporting
- No need for self-certification of anemometer
- Easy to use and calibrate
- User configurable operation
- Helps check digester process is running efficiently

Features

- Certified: ATEX, IECEx, CSA, MCERTS and UKAS calibration (ISO17025)
- Robust design for market leading reliability
- CH₄ and CO₂ accuracy $\pm 0.5\%$ after calibration
- Choice of user settings and simple gas reading function
- Measures % CH₄, CO₂ and O₂
- Modular and upgradeable
- 3 year warranty
- Stores and downloads readings
- User selected languages
- Event log
- Datalogging and profiling function
- Up to 6 gases monitored

Options (available at purchase or later)

- H₂S to 0-5,000ppm or 0-10,000ppm
- Additional gases including H₂ and NH₃
- Gas Analyser Manager software for data download
- External flow devices: anemometer (ATEX) / Pitot tubes
- ATEX certified temperature probe



Technical specifications

BIOGAS 5000

POWER SUPPLY

Battery type	Rechargeable nickel metal hydride battery pack (not user replaceable)
Battery life	Typical use 8 hours from fully charged
Battery Charger	Separate intelligent battery charger powered from mains supply (100 - 240V)
Charge time	Approximately 4 hours from complete discharge

GAS RANGES

Gases measured	CO ₂ and CH ₄	By dual wavelength infrared sensor with reference channel		
	O ₂	By internal electrochemical sensor		
	H ₂ S (optional)	By internal electrochemical sensor		
Standard gas cells	Cell	Range	Typical accuracy (range : accuracy)	Typical accuracy (range : accuracy)
	CH ₄	0-100%	0-70% : ±0.5% (vol)	70-100% : ±1.5% (vol)
	CO ₂	0-100%	0-60% : ±0.5% (vol)	60-100% : ±1.5% (vol)
	O ₂	0-25%	0-25% : ±1.0% (vol)	
Optional gas cells	Cell	Range	Typical accuracy	
	H ₂ S	0-50ppm	±1.5% FS	
	H ₂ S	0-200ppm	±2.0% FS	
	H ₂ S	0-500ppm	±2.0% FS	
	H ₂ S	0-1,000ppm	±2.0% FS	
	H ₂ S	0-5,000ppm	±2.0% FS	
	H ₂ S	0-10,000ppm	±5.0% FS	
	CO	0-500ppm	±2.0% FS	
	CO	0-1,000ppm	±2.0% FS	
	CO	0-2,000ppm	±2.0% FS	
	CO (H ₂) ⁺	0-2,000ppm	±1.0% FS	
	NH ₃	0-1,000ppm	±10.0% FS	
	H ₂	0-1,000ppm	±2.5% FS	
Typical accuracies	All typical accuracies quoted are after calibration			
+ Hydrogen compensated carbon monoxide measurement	Compensated for interference from up to 2,000ppm hydrogen. Hydrogen cross gas effect on carbon monoxide approximately 1%			
Response time, T90	CH ₄	≤ 10 seconds		
	CO ₂	≤ 10 seconds		
	O ₂	≤ 20 seconds		
	H ₂ S	≤ 30 seconds		
	CO	≤ 30 seconds		
	NH ₃	≤ 90 seconds		
	H ₂	≤ 90 seconds		

PUMP

Flow	550 ml/min typically
Flow fail point	-200 mbar vacuum - user settable
Maximum vacuum restart	-375 mbar approximately with flow rate of approx 80ml/min

Technical specifications

BIOGAS 5000, cont'd.

FACILITIES

Temperature measurement	-10°C to +75°C with optional probe
Temperature accuracy	±0.5°C with optional probe
Flow measurement	Via Pitot tube, orifice plate, or anemometer
Alarm	User selectable alarms
Communications	Via USB lead or wireless Bluetooth *
Relative pressure measurement	±500 mbar
Relative pressure accuracy	±4 mbar typically (should be zeroed before reading) to ±15 mbar max
Barometric pressure measurement	500 to 1500 mbar, ±5 mbar accuracy
Available memory	10 IDs *, 500 readings

ENVIRONMENTAL CONDITIONS

Operating temperature range	-10°C to +50°C
Atmospheric pressure range	700 to 1200 mbar
Relative humidity	0-95% non condensing
Case seal	IP65

PHYSICAL

Weight	1.6 kilograms
Size	L 220mm, W 155mm, D 60mm
Case material	ABS / polypropylene with rubber over-moulding
Keys	Alpha-numeric keypad with "tactile" membrane
Display	Ultra-clear high resolution 4.3" full colour TFT
Connections	Colour coded gas inlet, outlet and pressure ports. Waterproof USB port, anemometer and charger / temperature probe connections.
Gas sample filters	External user changeable 2.0µm ptfe water traps.

CERTIFICATION RATING

ATEX	II 2G Ex ib IIA T1 Gb (Ta = -10°C to +50°C)
MCERTS	MC/130240
ISO17025	Calibration to UKAS certificate number 4533
CSA	Ex ib IIA T1 (Ta= -10°C to +50°C) (Canada), AEx ib IIA T1 (Ta= -10°C to +50°C) (USA)

* Gas Analyser Manager software required.

Important note: The information in this document is correct at the time of generation. We do however, reserve the right to change the specification without prior notice as a result of continuing development.





Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.