



AIR QUALITY
CHECK ANALYSER

G150

New CO₂ analyser designed to monitor CO₂ for all indoor air quality applications. This unit has been developed to incorporate the latest technology and specification requirements, that provide the user with a fast, simple to use and accurate piece of environmental field kit.

Benefits

- Improved accuracy on CO₂ readings
- Quick verification of CO₂ levels for site audits
- Time saving with dual temperature probes
- Data logging for long term application
- Easy to read large well lit display
- Built in gas moisture removal

Features

- CO₂ 0- 10, 000 ppm
- Options for:
 - O₂ 0-100%
 - Dual temperature probes 0 - 50°C
 - Data storage and download
 - Humidity Sensor 0-100%

Applications

- General IAQ
- Environmental Site Audits
- HVAC Sytem approval
- Illegal immigrant control/ detection



Product Specifications

G100

GAS RANGES

Gases Measured	CO ₂	By custom dual wavelength infra-red cell reference channel
	O ₂ (Optional)	By internal electrochemical cell
Oxygen cell lifetime	Approximately 3 years in air	
Range	CO ₂ O ₂	0-10,000 ppm 0-100%
Measurement Accuracy	Gas	
	CO ₂	Accuracy ± (1% range) at reference conditions ¹ Temperature dependence ± 0.2% reading °C (typical at 1,000ppm CO ₂) Pressure dependence ± 0.02% of reading/hPa (typical at 1,000ppm CO ₂)
	O ₂	±1.0% Full Scale @ constant temperature and pressure ± 2.0% Full Scale over operating temperature range
Response time T ⁹⁰	CO ₂ O ₂	≤20 seconds ≤60 seconds

FACILITIES

¹ Conditions during factory calibration, typically 20 ° C, 100 mBar

Temperature (Optional)	x2 using optional probes 0 °C to +50.0 °C
Temperature accuracy, typical	± 0.2 °C over the range (± 0.1 °C between 32-44 °C) ±0.5 °C over the rest of range
Barometric pressure	800-1200 mbar
RH measurement (Optional)	RH Probe 0-100% RH non condensing
RH accuracy	+/- 1.5% RH across the range
Visual and audible alarm	User selectable CO ₂ and O ₂ alarm levels
Communications	USB type B mini-connector, HID device class
Data Storage	1000 readings sets + 270 events

ENVIRONMENTAL CONDITIONS

Operating temperature range	5 °C - 40 °C
Relative humidity	0-95% non condensing (RH Probe 0-100% non condensing)
Barometric pressure	± 200 mbar from calibration pressure

PHYSICAL

Weight	495 grams
Size	L 165mm, W 100mm, D 55 mm



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)1245 600560

Fax: +44 (0)1245 600030

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.