



Landfill

Applications

- Landfill gas monitoring
- Waste to energy
- Site investigation

Benefits

- Easy to use and calibrate
- Supports environmental legislation compliance
- Market leading reliability
- Standardises monitoring routines
- Easy transfer of data

Features

- Certified: ATEX, IECEx, MCERTS (applied for), CSA and UKAS calibration (ISO17025)
- Measures % CH₄, CO₂, and O₂
- Peak and previous readings shown
- Simultaneous display of all gases
- 3 year warranty
- CH₄ and CO₂ accuracy $\pm 0.5\%$ after calibration
- Modular and upgradeable
- Memory: 2,000 IDs*, 4,000 readings and 2,000 events* (* with GAM software)
- Event log

Options (available at purchase or later)

- Choice of additional gases including H₂S to 10,000ppm, and H₂ compensated CO
- Borehole gas flow (l/h)
- GPS / field navigator
- Gas Analyser Manager software for data download
- ATEX certified anemometer



Technical specifications

GA5000

POWER SUPPLY

Battery type	Rechargeable nickel metal hydride battery pack (not user replaceable)
Battery life	Typical use 8 hours from fully charged
Battery charger	Separate intelligent battery charger powered from mains supply (100-240V)
Charge time	Approximately 3 hours from complete discharge

GAS RANGES

Gases measured	CO ₂ and CH ₄	By dual wavelength infrared sensor with reference channel		
	O ₂	By internal electrochemical sensor		
	CO (hydrogen compensated), H ₂ S, NH ₃ and H ₂ (optional)	By internal electrochemical sensor		
	A full range of internal gas cells can be specified at the time of manufacture.			
Oxygen cell lifetime	Approximately 3 years in air			
other chemical cell lifetime	Suitable for sampling applications - not for continuous use			
Range	CH ₄ CO ₂ O ₂ CO H ₂ S	0-100% 0-100% 0-25% 0-2000ppm 0-5,000ppm or 0-10,000ppm		
Typical accuracy after calibration	CH ₄	0-70%	±0.5% (vol)	70-100% ±1.5% FS
	CO ₂	0-60%	±0.5% (vol)	60-100% ±1.5% FS
	O ₂	0-25%	±1.0% (vol)	
	CO	0-500ppm	± 2.0% FS	
	CO (H2)*	0-2000ppm	± 1.0% FS	
	H ₂ S	0-500ppm	± 2.0% FS	
		0-1000ppm	± 2.0% FS	
		0-5,000ppm	± 2.0% FS	
		0-10,000ppm	± 5.0% FS	
Response time, T90	CH ₄ CO ₂ O ₂ CO H ₂ S	≤ 10 seconds ≤ 10 seconds ≤ 20 seconds ≤ 30 seconds ≤ 30 seconds		
*Hydrogen compensated carbon monoxide measurement	Compensated for interference from up to 2,000ppm hydrogen. Hydrogen cross gas effect on CO approximately 1%.			

PUMP

Flow	550 ml/min typically
Flow fail point	-200 mbar vacuum - user settable
Maximum vacuum restart	-375 mbar approximately with flow rate of approximately 80ml/ min

Technical specifications

GA5000 cont'd.

FACILITIES

Temperature measurement	-10°C to +75°C with optional probe
Temperature accuracy	±0.5°C with optional probe
Flow from borehole	0-20 l/hr internal measurement
Flow from borehole accuracy	±0.3 l/hr
Alarm	User selectable alarm levels
Communications	Via USB lead or wireless Bluetooth *
Relative pressure measurement	±500 mbar
Relative pressure accuracy	±4 mbar typically (should be zeroed before reading) to ±15 mbar maximum
Barometric pressure measurement	500 to 1500 mbar, ±5 mbar accuracy
GPS sensor	Location and positioning
Available memory	2,000 IDs*, 4,000 readings, 2,000 events*

ENVIRONMENTAL CONDITIONS

Operating temperature range	-10°C to +50°C
Atmospheric pressure range	700 to 1200 mbar
Relative humidity	0-95% non condensing
Case seal	IP65

PHYSICAL

Weight	1.6 kilograms
Size	L 220mm, W 155mm, D 60mm
Case material	ABS/ polypropylene with rubber over-moulding
Keys	Alpha-numeric keypad with "tactile" membrane
Display	Ultra-clear high resolution 4.3" full colour TFT
Connections	Colour coded gas inlet, outlet and pressure ports. Waterproof USB port, anemometer and charger/ temperature probe connections.
Gas sample filters	External user changeable 2.0µm ptfe water traps.

CERTIFICATION RATING

ATEX	II 2G Ex ib IIA T1 Gb (Ta = -10°C to +50°C)
MCERTS	Applied for
ISO17025	Calibration to UKAS certificate number 4533
CSA	Ex ib IIA T1 (Ta= -10°C to +50°C) (Canada), AEx ib IIA T1 (Ta= -10°C to +50°C) (USA)

* Gas Analyser Manager software required

Important Note: The information in this document is correct at the time of generation. We do, however, reserve the right to change the specification without prior notice as a result of continuing development.





Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.