



# GASURVEYOR 500 SERIES



**The GMI Gasurveyor 500 Series is the most flexible range of gas detectors available today.**

By simple selection of hardware and software options, you can easily configure the product to suit your exact application.

## FEATURES

- Measures flammable, oxygen and toxic gases.
- Dual mode operation - Combustible Gas Indicator (CGI) / Confined Space Monitor (CSM).
- Rechargeable or alkaline battery options.
- Approved to European and North American safety standards.
- Extremely robust anti-static case.
- Simple to use.
- Built-in sampling pump as standard.
- Large LCD with automatic backlighting in low level light conditions.
- Compatible with the GMI range of Auto Calibration Systems.
- Audible / visual alarms for all gas ranges.
- Fault alarms for low flow, low battery etc.
- Probes for a wide range of applications.

### *Detection, Protection, Innovation*



**GMI. CONFIDENCE WHERE SAFETY IS CRITICAL.** Gas Measurement Instruments designs, manufactures and markets a wide range of the highest quality proven personal portable and fixed gas monitoring systems. GMI is an international brand with a worldwide network of distributors and dedicated service centers ensuring fast and effective turnaround on instrument calibration and repair. Our uncompromising engineering excellence, established in over half a century of leadership, enables us to meet the exacting demands of industries where safety is critical. By building and maintaining strong relationships with our customers, GMI understands the unique challenges of the diverse markets we serve. Today, our proud heritage of pioneering gas leak monitors and detectors is shaping the future of GMI.






# Gasurveyor 500 Series

In the Gasurveyor 500 range of instruments, GMI offer highly accurate and reliable gas detection instrumentation in an extremely robust, anti-static case. The following table allows you to select the 500 series instrument features to suit your specific needs. If you require further information please contact GMI.

GASURVEYOR 500 MODELS															
SENSORS	511	512	521	522	523	524	525	526	531	532	533	534	536	541	542
0-100% LEL	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
0-100% Gas	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
0-1000ppm CH4		X		X		X		X		X		X	X		X
0-25% O2			X	X					X	X	X	X		X	X
0-200ppm H2S					X	X			X	X			X	X	X
0-1000ppm CO							X	X			X	X	X	X	X

All models have Alarms and Datalogging enabled in Confined Space Mode (CSM).

TECHNICAL SPECIFICATION	
<b>Dimensions:</b>	180 x 95 x 105 mm / 7.1 x 3.7 x 4.1in.
<b>Weight:</b>	1.7 kg / 3.75 lbs
<b>Display:</b>	LCD with automatic backlighting
<b>Humidity:</b>	0-100% R.H. non-condensing
<b>Temperature:</b>	-20°C to +50°C (-4°F to +122°F)
<b>Alarms:</b>	Highly visible flashing LED Sounder: In excess of 80dB(A), typically 85db(A) @ 1m.
<b>Sampling:</b>	Integral pump with flow fail sensor; sample path is protected by a hydrophobic filter and automatic pump switch-off
<b>Battery:</b>	4 'D' size Alkaline Cells or Rechargeable Battery Pack
<b>Battery Life:</b>	15 hours Alkaline or 9 hours Rechargeable
<b>Construction:</b>	Moulded polypropylene case
<b>Rating:</b>	IP54 (Dust protected and splashproof)
<b>Response Time: (typical)</b>	LEL Flammable: 3 secs ( $t_{50}$ ); 5 secs ( $t_{90}$ ) Oxygen: 7 secs ( $t_{50}$ ) Toxics: 15 secs ( $t_{90}$ )
<b>Certification:</b>	ATEX  II 2 G EEx ia d IIC T4 (Ta = -20°C to +50°C) IECEX Ex ia d IIC T4 Gb (Ta = -20°C to +50°C)  UL Class I Groups A, B, C and D  CSA Class I Groups ABCD C22.2 No. 152



ORDERING INFORMATION AND ACCESSORIES		
44511/44511R	Gasurveyor 511 (Alkaline)	(Rechargeable)
44512/44512R	Gasurveyor 512 (Alkaline)	(Rechargeable)
44521/44521R	Gasurveyor 521 (Alkaline)	(Rechargeable)
44522/44522R	Gasurveyor 522 (Alkaline)	(Rechargeable)
44523/44523R	Gasurveyor 523 (Alkaline)	(Rechargeable)
44524/44524R	Gasurveyor 524 (Alkaline)	(Rechargeable)
44525/44525R	Gasurveyor 525 (Alkaline)	(Rechargeable)
44526/44526R	Gasurveyor 526 (Alkaline)	(Rechargeable)
44531/44531R	Gasurveyor 531 (Alkaline)	(Rechargeable)
44532/44532R	Gasurveyor 532 (Alkaline)	(Rechargeable)
44533/44533R	Gasurveyor 533 (Alkaline)	(Rechargeable)
44534/44534R	Gasurveyor 534 (Alkaline)	(Rechargeable)
44536/44536R	Gasurveyor 536 (Alkaline)	(Rechargeable)
44541/44541R	Gasurveyor 541 (Alkaline)	(Rechargeable)
44542/44542R	Gasurveyor 542 (Alkaline)	(Rechargeable)
13844	Simple 'low cost' Charger c/w Universal Plug	
Note: Above instruments supplied with - Harness; 4mm Hex Driver; User Handbook; 1.5m Clear Sample Line; Carrying Case; Standard Probe; Probe Handle Assembly; Sample Line Adaptor; 2 Packs of Cotton Filters.		



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



**UK Office**

**Keison Products,**

**P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.**

**Tel: +44 (0)330 088 0560**

**Fax: +44 (0)1245 808399**

**Email: [sales@keison.co.uk](mailto:sales@keison.co.uk)**

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.