

# Centrifuges

A focused range of compact, modern benchtop centrifuges for a variety of biomedical, biochemical and life science applications requiring centrifuging or a combination of centrifuging and mixing for microtubes and microtitre plates. Suitable for use in cold rooms and incubators (operating temperature range 4 to 40°C).

- General purpose low speed centrifuges
- Combined centrifuges/vortex mixers

LMC-3000






PCV-3000

PCV-2400

## Centrifuges » Models and specifications

### Centrifuges – models and specifications

- = standard
- = optional

		General purpose		Combined centrifuge/vortex mixer		
		LMC-3000		PCV-2400	PCV-3000	
		low speed		combi-spin, fixed speed	multi-spin, variable speed	
						
		13.5kg h: 235 mm d: 400 mm w: 470 mm	h: 115 mm d: 180 mm w: 225 mm	h: 115 mm d: 180 mm w: 225 mm		
G-force	G	–	700	1000		
Speed	rpm	1000 to 3000	2400	1000 to 3000		
Operation		continuous or timed	continuous up to 60 mins or short spins	continuous or timed		
Spin timer, with automatic switch-off		1 to 30 mins	–	1 sec to 99 mins		
Mix timer, with automatic switch-off		–	–	1 to 20		
Vortex mixing intensity	3-stage adjustment	–	–	soft, medium, hard		
Cycle regulation		–	–	1 to 999		
Capacity		–	●	●		
		12 x 1.5/2.0 ml microtubes	–	–		
		12 x 0.5 ml plus 12 x 0.2 ml microtubes	●	●		
		12 x 10-15 ml tubes, round end, no cap*	●	–		
Display		2 line x 16 character LCD	–	2 line x 16 character LCD		
Input voltage	V dc	–	–	12		
	V ac	230 (50-60 Hz)	220-240/110-120 (50-60 Hz)			
External power supply		–	–	●		
Ambient temperature range	°C		4 to 40			

### Accessories for PCV-2400/PCV-3000

<b>R-6</b> interchangeable centrifuge rotor for 6 x 50 ml tubes, with cap, conical end	●	–	–
<b>R-12-15</b> interchangeable centrifuge rotor for 12 x 15 ml tubes, with cap, conical end	●	–	–
<b>R-2</b> interchangeable centrifuge rotor for 2 x 96-well microtitre plates	●	–	–
<b>PR2-05</b> interchangeable centrifuge rotor for 8 x 1.5/ 2.0 ml plus 8 x 0.5 ml microtubes	–	●	●
<b>PR2-05-02</b> interchangeable centrifuge rotor for 6 x 1.5/ 2.0 ml plus 6 x 0.5 ml plus 6 x 0.2 ml microtubes	–	●	●
<b>PSR-16</b> interchangeable centrifuge rotor for 2 x 8-well 0.2 ml microtube strips	–	●	●

\* with R-12-10 rotor



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



**UK Office**

**Keison Products,**

**P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.**

**Tel: +44 (0)1245 600560**

**Fax: +44 (0)1245 600030**

**Email: [sales@keison.co.uk](mailto:sales@keison.co.uk)**

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.