

Data Sheet

Mixing / Overhead Stirrers



EUROSTAR power basic

Powerful laboratory stirrer for tasks up to the - high viscosity - range.

- Constant speed by microprocessor control
- Infinitely adjustable without gear shifting
- Slim casing
- Quiet operation
- Safety circuit
- Non-locking, overload capabilities
- Push-through agitator shafts
- Enhanced safety as a result of smooth start
- Analog recording of speed parameters is possible

Accessories: R 1342 Propeller stirrer, 4-bladed, R 1303 Dissolver stirrer, R 1330 Anchor stirrer, R 301 Stirring shaft protection, R 271 Boss head clamp, R 1345 Propeller stirrer, 4-bladed, R 1375 Paddle stirrer, R 1381 Propeller stirrer, 3-bladed, R 2722 H-Stand, R 1311 Turbine stirrer, FK 1 Flexible coupling, R 1389 (PTFE-coated) Propeller stirrer, 3-bladed, RH 5 Strap clamp, R 1300 Dissolver stirrer, R 1312 Turbine stirrer, R 1302 Dissolver stirrer, R 1352 Centrifugal stirrer, R 1382 Propeller stirrer, 3-bladed, R 2723 Telescopic stand, R 1331 Anchor stirrer, R 1313 Turbine stirrer, R 1355 Centrifugal stirrer

Technical Data	
Stirring quantity max. (H ₂ O) [l]	40
Motor rating input [W]	130
Motor rating output [W]	110
Speed display	scale
Speed range [rpm]	50 - 2000
Viscosity max. [mPas]	50000
Output max. at stirring shaft [W]	105
Permissible ON time [%]	100
Torque max. at stirring shaft [Ncm]	60
Torque max. at stirring shaft at 60 1/min (overload) [Ncm]	60
Torque max. at stirring shaft at 100 1/min [Ncm]	60
Torque max. at stirring shaft at 1.000 1/min [Ncm]	60
Speed control	stepless
Stirring element fastening	chuck
Chuck range min. diameter [mm]	0.5
Chuck range max. diameter [mm]	10
Hollow shaft, inner diameter [mm]	11
Hollow shaft (push-through & when stopped)	yes
Fastening on stand	extension arm
Extension arm diameter [mm]	16
Extension arm length [mm]	200
Torque display	no
Nominal torque [Nm]	0.6
Dimensions (W x H x D) [mm]	80 x 253 x 190
Weight [kg]	3.8
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 42
RS 232 interface	no
Analog output	yes
Voltage [V]	230 / 115 / 100
Frequency [Hz]	50/60
Power input [W]	130
Ident. No.	2572200



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.