

Data Sheet

Mixing / Overhead Stirrers



EUROSTAR power control-visc P1

Powerful, digital laboratory stirrer for tasks up to the high viscosity range.

- Max. torque at chuck 100 Ncm
- Constant speed by microprocessor control
- Infinitely adjustable without gear shifting
- Slim casing
- Quiet operation
- Safety circuit
- Non-locking, overload capabilities
- Push-through agitator shafts
- Enhanced safety as a result of smooth start
- Digital display presents rated- and actual- speed
- Integrated torque trend display for viscosity control
- Analog interface for recording speed and torque
- RS 232 interface
- Software labworldsoft® is available to control and document all measuring values via PC

Accessories: R 1385 Propeller stirrer, 3-bladed, R 1313 Turbine stirrer, R 1342 Propeller stirrer, 4-bladed, R 1330 Anchor stirrer, R 301 Stirring shaft protection, R 271 Boss head clamp, labworldsoft®, R 1345 Propeller stirrer, 4-bladed, R 1375 Paddle stirrer, R 1381 Propeller stirrer, 3-bladed, R 2722 H-Stand, R 1311 Turbine stirrer, R 1389 (PTFE-coated) Propeller stirrer, 3-bladed, R 1333 Anchor stirrer, RH 5 Strap clamp, R 1312 Turbine stirrer, R 1376 Paddle stirrer, R 1382 Propeller stirrer, 3-bladed, R 2723 Telescopic stand, R 1331 Anchor stirrer, R 1388 Propeller stirrer, 3-bladed

Technical Data	
Stirring quantity max. (H ₂ O) [l]	60
Motor rating input [W]	153
Motor rating output [W]	134
Speed display	LCD
Speed range [rpm]	50 - 1200
Viscosity max. [mPas]	70000
Output max. at stirring shaft [W]	126
Permissible ON time [%]	100
Torque max. at stirring shaft [Ncm]	100
Torque max. at stirring shaft at 60 1/min (overload) [Ncm]	100
Torque max. at stirring shaft at 100 1/min [Ncm]	100
Torque max. at stirring shaft at 1.000 1/min [Ncm]	100
Speed control	stepless
Stirring element fastening	chuck
Chuck range min. diameter [mm]	0.5
Chuck range max. diameter [mm]	10
Hollow shaft, inner diameter [mm]	11
Hollow shaft (push-through & when stopped)	yes
Fastening on stand	extension arm
Extension arm diameter [mm]	16
Extension arm length [mm]	200
Torque display	yes
Nominal torque [Nm]	1
Torque measurement	trend
Dimensions (W x H x D) [mm]	80 x 253 x 190
Weight [kg]	4
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 42
RS 232 interface	yes
Analog output	yes
Voltage [V]	230
Frequency [Hz]	50/60
Power input [W]	153
Ident. No.	3330000



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.