



KS 130 basic

Small, quiet shaker ensures long life with ideal swivel motion, for a maximum shaking weight of 2 kg.

- Electronic adjustment of speed and timer
- LED display for speed and time adjustment
- Wide range of attachment combinations makes it possible to use almost all shapes and sizes of vessels
- Attachments are not included, please order separately

Accessories: STICKMAX, AS 2.2 Fixing clips, AS 2.3 Fixing clips, AS 2.4 Fixing clips, AS 2.5 Fixing clips, AS 130.4 Test tube support, H 11 Mains cable CH plug, AS 130.1 Universal attachment, AS 130.2 Fixing clip attachment, AS 130.3 Dish attachment, H 11 Mains cable Euro plug, H 11 Mains cable USA plug, AS 2.1 Fixing clips, H 11 Mains cable UK plug

Technical Data

Type of movement	orbital
Shaker diameter [mm]	4
Permissible shaking weight (incl. attachment) [kg]	2.0
Motor rating input [W]	45
Motor rating output [W]	10
Permissible ON time [%]	100
Speed min (adjustable) [rpm]	80
Speed range [rpm]	0 - 800
Speed display	LED line
Timer	yes
Timer display	LED line
Time setting range [min]	5 - 50
Operating mode	timer and continuous operation
Shaking table lock	no
Dimensions (W x H x D) [mm]	270 x 98 x 316
Weight [kg]	8.8
Permissible ambient temperature [°C]	5 - 50
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 21
RS 232 interface	no
Analog output	no
Voltage [V]	220 - 240 / 100 - 120
Frequency [Hz]	50/60
Power input [W]	45
Ident. No.	2980000



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.