



### KS 4000ic control

New innovative incubator shaker design with built-in cooler allowing unattended operation in a temperature-controlled environment.

- Large LED display for speed and time settings
- Controls with antimicrobial coating for reduction of bacteria
- Integrated PID temperature control (use of two PT 1000 temperature sensors)
- Junction box in the workspace for connection of an additional temperature sensor e.g. PT 1000.60 (included with delivery)
- Electronic temperature and speed control
- Electronic timer switch: 0 - 999 h (set by the minute or by the hour)
- With built-in cooling spiral for connection to an external cooling unit e.g. KV 600
- Unit stops automatically when hood is lifted
- Collecting tray with drain hose on rear of unit
- Simple operation
- All functions can be controlled and documented using the labworldsoft® software
- Attachments not included - please order accessories as required

Accessories: AS 4000.1 Universal attachment, STICKMAX, AS 4000.2 Fixing clip attachment, AS 4000.3 Dish attachment, AS 2.1 Fixing clips, AS 2.2 Fixing clips, AS 2.3 Fixing clips, AS 2.4 Fixing clips, AS 2.5 Fixing clips, AS 2.6 Fixing clips, KV 600 cooling water supply, PT 1000.60 Temperature sensor, stainless steel, labworldsoft®, PC 1.1 Cable, H 11 Mains cable Euro plug, H 11 Mains cable UK plug, H 11 Mains cable CH plug, H 11 Mains cable USA plug

Technical Data	
Type of movement	orbital
Shaker diameter [mm]	20
Permissible shaking weight (incl. attachment) [kg]	20
Motor rating input [W]	82
Motor rating output [W]	24
Permissible ON time [%]	100
Speed min (adjustable) [rpm]	10
Speed range [rpm]	10 - 500
Speed display	LED
Timer	yes
Timer display	7 segment LED
Time setting range [min]	1 - 59940
Operating mode	timer and continuous operation
Touch function	no
Shaking table lock	no
Working with microtiter plates	no
Heating temperature range [°C]	room temp. +5° - 80
Heat output [W]	1000
Temperature display	yes
Temp. stability (0,2l H2O; RT 25°C, T=37°C) [±K]	0.1
Temperature range (inlet T>3°C) [°C]	12 - 80
Dimensions (W x H x D) [mm]	580 x 525 x 750
Weight [kg]	55
Permissible ambient temperature [°C]	15 - 32
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 30
RS 232 interface	yes
Voltage [V]	230
Frequency [Hz]	50/60
Power input [W]	1120
<b>Ident. No.</b>	<b>3510100</b>



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



**UK Office**

**Keison Products,**

**P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.**

**Tel: +44 (0)330 088 0560**

**Fax: +44 (0)1245 808399**

**Email: [sales@keison.co.uk](mailto:sales@keison.co.uk)**

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.