

Data Sheet

Mixing / Shakers



KS 501 digital

Low profile laboratory shaker with a pleasant design, large mounting surface and load capacity of up to 15 kg.

- Infinitely variable speed control of 0 - 300 rpm
- Digital display
- Orbital diameter 30 mm
- Ideal for vessels with a volume of more than 250 ml, e.g. round flasks, Erlenmeyer flasks, culture flasks and culture bottles
- Ideal for biological and microbiological growth tests, for the production of stock solutions
- Guaranteed continuous operation (endless) even under extreme loads
- Includes timer
- Attachments are not included, please order separately

Accessories: STICKMAX, AS 2.2 Fixing clips, AS 2.3 Fixing clips, AS 2.4 Fixing clips, AS 2.5 Fixing clips, AS 501.5 Dish attachment, H 11 Mains cable CH plug, H 11 Mains cable UK plug, AS 2.6 Fixing clips, AS 501.4 Fixing clip support, H 11 Mains cable Euro plug, H 11 Mains cable USA plug, AS 2.1 Fixing clips, AS 501.1 Universal attachment

Technical Data	
Type of movement	orbital
Shaker diameter [mm]	30
Permissible shaking weight (incl. attachment) [kg]	15
Motor rating input [W]	70
Motor rating output [W]	19
Permissible ON time [%]	100
Speed range [rpm]	0 - 300
Speed display	LED
Timer	yes
Timer display	scale
Time setting range [min]	1 - 56
Operating mode	timer and continuous operation
Shaking table lock	no
Dimensions (W x H x D) [mm]	505 x 120 x 585
Weight [kg]	26
Permissible ambient temperature [°C]	5 - 50
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 21
RS 232 interface	no
Analog output	no
Voltage [V]	230 / 115 / 100
Frequency [Hz]	50/60
Power input [W]	74
Ident. No.	2526400



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.