

Data Sheet

Mixing / Overhead Stirrers



RW 28 basic

Powerful, mechanically controlled stirrer. Suitable for quantities up to 80 l (H₂O) for use in laboratories and pilot plant stations.

- Two speed ranges for highly viscous media and for intensive mixing
- Push-through agitator elements

Accessories: R 1385 Propeller stirrer, 3-bladed, R 301.1 Support holder, R 1355 Centrifugal stirrer, R 301 Stirring shaft protection, R 271 Boss head clamp, R 1345 Propeller stirrer, 4-bladed, R 1375 Paddle stirrer, R 2722 H-Stand, FK 1 Flexible coupling, R 1333 Anchor stirrer, RH 5 Strap clamp, R 1300 Dissolver stirrer, R 1302 Dissolver stirrer, R 1376 Paddle stirrer, R 2723 Telescopic stand, R 1331 Anchor stirrer, R 1313 Turbine stirrer, R 1388 Propeller stirrer, 3-bladed

Technical Data	
Stirring quantity max. (H ₂ O) [l]	80
Motor rating input [W]	220
Motor rating output [W]	90
Speed display	scale
Speed range [rpm]	60 - 1400
Viscosity max. [mPas]	50000
Output max. at stirring shaft [W]	90
Permissible ON time [%]	100
Torque max. at stirring shaft [Ncm]	900
Torque max. at stirring shaft at 60 1/min (overload) [Ncm]	1144
Torque max. at stirring shaft at 100 1/min [Ncm]	900
Torque max. at stirring shaft at 1.000 1/min [Ncm]	86
Speed range I (50 Hz) [rpm]	60 - 400
Speed range II (50 Hz) [rpm]	240 - 1400
Speed range I (60 Hz) [rpm]	72 - 480
Speed range II (60 Hz) [rpm]	288 - 1680
Speed control	stepless
Stirring element fastening	chuck
Chuck range min. diameter [mm]	1
Chuck range max. diameter [mm]	10
Hollow shaft, inner diameter [mm]	10.5
Hollow shaft (push-through & when stopped)	yes
Fastening on stand	extension arm
Extension arm diameter [mm]	16
Extension arm length [mm]	145
Torque display	no
Nominal torque [Nm]	9.0
Dimensions (W x H x D) [mm]	123 x 364 x 252
Weight [kg]	7.4
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 42
RS 232 interface	no
Analog output	no
Voltage [V]	220 - 240 / 115 / 100
Frequency [Hz]	50/60
Power input [W]	220
Ident. No.	2760000



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.