

Data Sheet

Mixing / Overhead Stirrers



RW 47 D

The most powerful IKA® stirrer for laboratories, pilot plant stations and small-scale production.

- For stirring tasks up to 200 l (H₂O)
- Two speed ranges for highly viscous media and intensive mixing
- Cables and plugs not included in delivery

Accessories: SI 400 Safety switch, R 302 Stirring shaft protection, R 1388 Propeller stirrer, 3-bladed, R 2302 Propeller stirrer, 4-bladed, R 1355 Centrifugal stirrer, SI 474 Fixing device, R 2311 Paddle stirrer, R 1345 Propeller stirrer, 4-bladed, R 474 Telescopic stand, R 1333 Anchor stirrer, SI 472 Fixing device, R 1302 Dissolver stirrer, R 472 Floor stand, R 1376 Paddle stirrer, R 1385 Propeller stirrer, 3-bladed

Technical Data	
Stirring quantity max. (H ₂ O) [l]	200
Motor rating input [W]	513
Motor rating output [W]	370
Speed display	scale
Speed range [rpm]	57 - 1300
Viscosity max. [mPas]	100000
Output max. at stirring shaft [W]	300
Permissible ON time [%]	100
Torque max. at stirring shaft [Ncm]	3000
Torque max. at stirring shaft at 60 1/min (overload) [Ncm]	4642
Torque max. at stirring shaft at 100 1/min [Ncm]	3000
Torque max. at stirring shaft at 1.000 1/min [Ncm]	285
Speed range I (50 Hz) [rpm]	57 - 275
Speed range II (50 Hz) [rpm]	275 - 1300
Speed control	stepless
Stirring element fastening	chuck
Chuck range min. diameter [mm]	3
Chuck range max. diameter [mm]	16
Hollow shaft, inner diameter [mm]	13
Hollow shaft (push-through & when stopped)	no
Fastening on stand	flange
Torque display	no
Nominal torque [Nm]	30
Dimensions (W x H x D) [mm]	145 x 445 x 340
Weight [kg]	15
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 54
RS 232 interface	no
Analog output	no
Voltage [V]	3 x 400 Y / 3 x 230
Frequency [Hz]	50
Power input [W]	513
Ident. No.	1602000



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.