

Data Sheet

Crushing / Dispersers



T 10 basic ULTRA-TURRAX®

New, competitively priced dispersing instrument for volumes of 0,5 to 100 ml. A wide speed range allows you to work at high circumferential speeds even with small rotor diameters. Perfect ergonomic finish.

- Immense speed stability with various media thanks to high performance 125 Watt drive
- Ideal for manual operation thanks to its light weight and ergonomic form
- Extremely mobile thanks to direct mains operation (no transformer required)
- Stainless steel dispersing elements (5 mm, 8 mm and 10 mm diameter) can be cleaned quickly and easily as they can be dismantled without tools
- Plastic disposable dispersing elements in two sizes, particularly suitable for PCR analysis
- Quick-release coupling makes changing the dispersing elements easy

Included with delivery:

- clamp R 200
 - storage case, empty (for drive, dispersing elements and spare seals)
- Please order dispersing elements separately

Accessories: S 10 N - 5 G Dispersing element, S 10 N - 8 G Dispersing element, S 10 N - 10 G Dispersing element, S 10 D - 7G - KS - 65 Dispersing element, S 10 D - 7G - KS - 110 Dispersing element, R 200 Clamp, H 44 Boss head clamp, R 104 Stand

Technical Data

Motor rating input [W]	125
Motor rating output [W]	75
Volume range min. (H ₂ O) [l]	0.0005
Volume range max. (H ₂ O) [l]	0.1
Viscosity max. [mPas]	5000
Speed range [rpm]	8000 - 30000
Speed display	scale
Speed control	stepless
Noise without element [dB(A)]	65
Extension arm diameter [mm]	8
Extension arm length [mm]	100
Process type	batch
Power-on time ON [min]	10
Power-on time OFF [min]	5
Dimensions (W x H x D) [mm]	46 x 201 x 57
Weight [kg]	0.4
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 30
Voltage [V]	230 / 115 / 100
Frequency [Hz]	50/60
Power input [W]	125
Ident. No.	3420000



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.