

Data Sheet

Crushing / Dispersers



T 25 digital ULTRA-TURRAX®

The new ULTRA -TURRAX® high-performance disperser by IKA®

- For volumes of 1 to 2.000 ml (H₂O)
- The spectrum of applications ranges from homogenizing waste water samples to the use in laboratory reactors, to dispersion tasks under vacuum / pressure and sample preparation in medical diagnostics
- Three types of shaft bearings
- Standard version with digital display
- Rotor-Stator configurations have thirty years of proven, guaranteed comparability of test results

Accessories: S 25 N - 8 G Dispersing element, S 25 N - 10 G Dispersing element, S 25 N - 18 G Dispersing element, S 25 N - 25 G Dispersing element, S 25 N - 25 F Dispersing element, S 25 NK - 19 G Dispersing element, S 25 KV - 18 G Dispersing element, S 25 KV - 25 G Dispersing element, S 25 KV - 25 F Dispersing element, S 25 D - 10 G - KS Dispersing element (10 pcs), S 25 D - 14 G - KS Dispersing element (10 pcs), S 18 / 2 -ET 0 Disposable tube, Silentsream, R 1827 Plate stand, RH 3 Strap clamp, R 1826 Plate stand, R 1825 Plate stand, R 182 Boss head clamp

Technical Data	
Motor rating input [W]	500
Motor rating output [W]	300
Volume range min. (H ₂ O) [l]	0.001
Volume range max. (H ₂ O) [l]	2
Viscosity max. [mPas]	5000
Speed range [rpm]	3400 - 24000
Speed deviation [%]	1
Speed display	LED
Speed control	stepless
Noise without element [dB(A)]	73
Extension arm diameter [mm]	13
Extension arm length [mm]	175
Process type	batch
Dimensions (W x H x D) [mm]	65 x 240 x 80
Weight [kg]	1.6
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 20
RS 232 interface	no
Analog output	no
Voltage [V]	220 - 240 / 100 - 120
Frequency [Hz]	50/60
Power input [W]	500
Ident. No.	3565000



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.