



T 50 basic ULTRA-TURRAX®

High-performance dispersing instrument for volumes from 0.25 - 30 l (H₂O).

- Three types of shaft bearings
- Several rotor-stator configurations
- Agitator shaft R 50 allows the use of the T 50 basic as a high-speed stirrer (not included in delivery)
- Infinitely variable speed control, for continuous operation
- Reproducible operations due to constant speed even with viscosity changes
- Large selection of dispersing elements
- Plug-in connectors facilitate exchange of dispersing elements
- Electronic safety circuit and smooth start
- As standard, the T 50 basic is equipped with a connection for the revolution counter
- Wide range of dispersing elements (not included in delivery)

Accessories: S 50 N - G 45 G Dispersing element, S 50 N - G 45 M Dispersing element, S 50 N - G 45 F Dispersing element, R 50 stirring shaft «high speed», R 1405 Propeller, R 1402 Dissolver, S 50 N - W 80 SMK Jet mixer head, S 50 N - W 65 SK Cutting head, R 271 Boss head clamp, R 2722 H-Stand, RH 5 Strap clamp, R 2723 Telescopic stand

Technical Data	
Motor rating input [W]	1100
Motor rating output [W]	700
Volume range min. (H ₂ O) [l]	0.25
Volume range max. (H ₂ O) [l]	30
Viscosity max. [mPas]	5000
Speed range [rpm]	500 - 10000
Speed deviation [%]	1
Speed control	stepless
Speed display	scale
Noise without element [dB(A)]	72
Extension arm diameter [mm]	16
Extension arm length [mm]	220
Process type	batch
Dimensions (W x H x D) [mm]	125 x 367 x 120
Weight [kg]	6
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 20
Voltage [V]	230
Frequency [Hz]	50/60
Power input [W]	1100
Ident. No.	3783500



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.