

Data Sheet

Crushing / Dispersers



T 65 D ULTRA-TURRAX®

The high-performance T 65 D dispersing instrument has been designed for typical pilot plant stations quantities from 2 - 50 l (H₂O).

- Three rotor-stator configurations for a variety of applications (not included with delivery)
- Plug-in connectors facilitate exchange of dispersing elements
- Dispersing instruments for the production area: ask for our process technology catalogs
- Cables and plugs not included with delivery

Accessories: S 65 KG - HH - G 65 F Dispersing element, S 65 KG - HH - G 65 G Dispersing element, S 65 KG - HH - G 65 M Dispersing element, T 653 Telescopic stand

Technical Data	
Motor rating input [W]	1800
Motor rating output [W]	1500
Volume range min. (H ₂ O) [l]	2
Volume range max. (H ₂ O) [l]	50
Viscosity max. [mPas]	5000
Speed max. [rpm]	7200
Noise without element [dB(A)]	75
Process type	batch
Dimensions (W x H x D) [mm]	190 x 380 x 580
Weight [kg]	28
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 54
Voltage [V]	3 x 400 Y / 3 x 230
Frequency [Hz]	50
Power input [W]	1800
Ident. No.	1602800



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.