



NEW PRESSURE REDUCER!

BD mini

[Short Duration Compressed Air Breathing Apparatus]

The compressed air breathing apparatus BD mini, which now features a redesigned, maintenance-friendly pressure reducer, is especially suited for short duration work in confined spaces.

Its compact size and versatile design permit the use of various carrying modes. Thus the apparatus is ideal for sites that can only be reached through narrow entry openings or for work in confined spaces.

Of course, the BD mini can also be carried on the back like a “large” compressed air breathing apparatus and can also be used for brief explorations or inspection tours.

With a coupling for compressed airline breathing apparatus [available as accessory], the BD mini can be connected to a stationary air source.

This permits the operator to remain at the worksite for longer durations. The BD mini supplies air for the approach, as well as for the return.





Hip carrying mode

With hip belt and shoulder strap; compressed air cylinder suspended between legs [for entry].



Back carrying mode

With hip belt only; compressed air cylinder carried diagonally across the back.



Shoulder carrying mode

With shoulder strap; compressed air cylinder suspended laterally.

[Design]

Depending on the lung governed demand valve used, the BD mini can be operated as a normal pressure or a positive pressure apparatus.

The base of the BD mini is the carrying plate. The apparatus has an easily adjustable harness. The hip belt and shoulder strap can be attached through the slots provided in the carrying plate, without requiring the use of any special tools. This user-friendly method allows the carrying mode to be adapted to individual requirements.

The apparatus is supplied from the factory with the hip belt and shoulder strap already adjusted for the back carrying mode. The carrying plate is also provided with several slots of varying dimensions, permitting the trouble-free mounting of the pressure reducer. In this way, the pressure reducer can always be placed in the optimum position, regardless of the carrying mode selected by the operator.

[Function]

The pressure reducer is designed to be connected to 200 or 300 bar compressed air cylinders.

The warning signal at the pressure reducer is high pressure controlled and medium pressure dosed. Thus a loud, constant signal sounds during the total alarm. The great advantage of this is that the warning device functions injector-less: i.e. the input of ambient air is not required to discharge the warning signal.

Also on the pressure reducer is the pressure gauge line with a large luminescent and pivotable pressure gauge, as well as the medium pressure line to connect the lung governed demand valve.

The compressed air cylinder is fastened onto the carrying plate with a cylinder retaining strap. The strap's universal length permits the use of cylinders of various sizes. A large, handy tightener, fitted with a locking device permits the swift and easy exchange of cylinders.

[Features and Benefits]

- small and lightweight
- with 2 l/300 bar composite cylinder, weight less than 5 kg
- various carrying modes
- especially suited for use in confined spaces
- innovative state-of-the-art 1st stage pressure reducer with new, modern design
- for use with normal or positive pressure

[Accessories]

A special Y-piece with nonreturn valve permits the use of the BD mini combined with a compressed airline breathing apparatus. The Y-piece attaches to the medium pressure coupling. The compressed air cylinder must be closed during this time.

The optional Automatic Switch Valve connects a compressed airline to a BD mini. This ensures a continuous supply of air in case the external air source [e.g. factory airline] fails. The ASV switches automatically to the air source with higher pressure. The compressed air cylinder stays open.



Water-tight and self-luminescent pressure gauge:
easy to read in any position

Cylinder holder:
easily adjusted to various cylinder sizes

Carrying plate:
handy to carry, comfortable to wear

Harness:
easy to clean

New pressure reducer:
high performance, reduced weight, low maintenance

Injector-less warning whistle:
no danger of parts freezing over



[Demand Valves]

AutoMaXX series

AutoMaXX-AE:

Positive pressure demand valve with thread connection M 45 x 3 to EN 148-3.

AutoMaXX-AS:

Positive pressure lung governed demand valve with MSA plug connector.

AutoMaXX-AS-B:

Features a By Pass valve for constant air flow.

AutoMaXX-N:

Normal pressure lung governed demand valve with standard round thread according to EN 148-1.

All versions available with rubber line [extension: G]



AutoMaXX-AE

LA 96 & 88 series

LA 96-AE:

Small, light-weight positive pressure demand valve: the first breath automatically switches the positive pressure.

For doffing, loss of air is prevented by simply switching it back into readiness [normal pressure]. It connects to the face mask by a threaded handwheel with the EN 148-3 thread M 45 x 3.

LA 96-AS:

The LA 96-AS is identical to the LA 96-AE in construction and function. The connection to the face mask is a quick connect coupling, just push and breathe.

LA 96-N:

The smallest and lightest demand valve for normal pressure. Servo-assisted, it delivers the breathing air almost resistance-free. With handwheeled thread connection to EN 148-1 [round thread].

LA 88-AE/AS/N:

The same features the LA 96 series but medium pressure line of rubber material to stand harsh conditions.



LA 96-AS



Y-piece attached to the medium pressure coupling of BD mini

[Technical Data]

Operating pressure 300 bar

Initiating pressure of warning signal
105 ± 5 bar

Weight [Basic apparatus] approx. 2.1 kg

Materials

Carrying plate Polycarbonate, self-extinguishing
 Harness Aramid/Nomex, self-extinguishing
 Pressure reducer Brass, nickel plated, chrome plated
 Fittings Stainless steel, Thermoplast, self-extinguishing

[Accessories]

D4066857 Y-Piece
 D4066700 Automatic Switch Valve


Compressed Air Cylinders – Steel

D5103963 2l/200 bar, full
 D5103983 2l/200 bar, empty
 D5103964 2l/300 bar, full
 D5103984 2l/300 bar, empty

Compressed Air Cylinders – Composite

D5103969 2l/300 bar, full
 D5103974 2l/300 bar, empty
 10050853 3l/300 bar, full, with airflow restrictor
 10058821 3l/300 bar, empty, with airflow restrictor

[Ordering Information]

Basic Unit	Demand Valves	Facepieces
D4075713 BD mini 	NORMAL- D4074808 LA 83 10023686 AutoMaXX-N D4075960 LA 88-N 10036274 AutoMaXX-N-G D4075852 LA 96-N	D2055000 3S [EN 148-1] D2055718 3S Silicone [EN 148-1] D2056700 Ultra Elite [EN 148-1] D2056718 Ultra Elite Silicone [EN 148-1]
	POSITIVE-PRESSURE D4075906 LA 88-AS 10023688 AutoMaXX-AS D4075850 LA 96-AS 10036272 AutoMaXX-AS-G 10038296 AutoMaXX-AS-B 10038410 AutoMaXX-AS-B-G	For the demand valve LA 88-AS and LA 96-AS D2055751 3S-PS D2055764 3S-PS Silicone D2056751 Ultra Elite-PS D2056764 Ultra Elite-PS Silicone For the demand valve AutoMaXX-AS 10031422 3S-PS-MaXX 10031388 3S-PS-MaXX Silicone 10031385 Ultra Elite-PS-MaXX 10031384 Ultra Elite-PS-MaXX Silicone
	D4075909 LA 88-AE 10023687 AutoMaXX-AE D4075851 LA 96-AE 10036271 AutoMaXX-AE-G	D2055741 3S-PF [EN 148-3] D2055763 3S-PF Silicone [EN 148-3] D2055741 Ultra Elite-PF [EN 148-3] D2056763 Ultra Elite-PF Silicone [EN 148-3]

AE / PF = Connector M 45 x 3 · AS / PS = MSA Quick Connector for LA 88- and LA 96-AS · B = By pass valve · G = Rubber line · MaXX = Plug connector for AutoMaXX-AS
 N = Normal pressure. Other full face mask versions are available on request.



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)1245 600560

Fax: +44 (0)1245 600030

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.