



## Testo 410 - Wind or air flow, temperature and humidity



- Available in two models:  
**Testo 410-1** wind or air flow and temperature  
**Testo 410-2** wind or air flow, temperature and humidity
- Integrated 40 mm vane
- Timed mean value calculation
- Hold function and min./max. values
- Windchill calculation for outdoor areas

### Technical data

#### Flow velocity

Measuring range: 0.4 to 20 m/s

Resolution: 0.1 m/s

Accuracy:  $\pm (0.2 \text{ m/s} + 2\% \text{ of m.v.})$

Units: m/s, km/h, fpm, mph, knots, perceived

temperature °C/°F

(windchill), Beaufort

#### Temperature

Measuring range: -10 to 50 °C

Resolution: 0.1 °C

Accuracy:  $\pm 0.5 \text{ °C}$

Units: °C/°F

#### Humidity (testo 410-2 only):

Measuring range: 0 to 100 %rh

Resolution: 0.1 %rh

Accuracy:  $\pm 2.5 \text{ %rh}$   
(5 to 95 %rh)

Units: %rh, wet bulb, dewpoint

Oper. temp.: -10 to 50 °C

Battery type: Alkaline (2 x AAA)

Battery life: testo 410-1: 100 h.  
testo 410-2: 60 h.  
(average, without display illumination)

#### Dimensions

(incl. protective cap): 133 x 46 x 25 mm

#### Included in delivery:

Calibration protocol · Wrist strap

Belt holder · Protective cap · Batteries

410-1: Part no. 0560 4101

410-2: Part no. 0560 4102



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



**UK Office**

**Keison Products,**

**P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.**

**Tel: +44 (0)1245 600560**

**Fax: +44 (0)1245 600030**

**Email: [sales@keison.co.uk](mailto:sales@keison.co.uk)**

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.