



## Testo 810 - Air and surface temperature in one instrument



- Surface temperature IR measurement with 1-point laser spot marking and 6:1 optics
- Air temperature measurement
- Display of differential temperature e.g. between window and air
- Hold function and max./min. values

### Technical data

#### Surface temperature:

Measuring range: -30 to 300 °C

Resolution: 0.1 °C

Accuracy:  $\pm 2.0$  °C  
(-30 to +100 °C)  
 $\pm 2\%$  of m.v.  
(remaining range)

Optics: 6:1

#### Air temperature:

Measuring range: -10 to 50 °C

Resolution: 0.1 °C

Accuracy:  $\pm 0.5$  °C

Units: °C/°F

Oper. temp.: -10 to 50 °C

Battery type: Alkaline (2 x AAA)

Battery life: 50 h. (average, without display illumination)

#### Dimensions

(incl. protective cap): 119 x 46 x 25 mm

#### Included in delivery:

Calibration protocol · Wrist strap

Belt holder · Protective cap · Batteries

Part no. 0560 0810



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



**UK Office**

**Keison Products,**

**P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.**

**Tel: +44 (0)1245 600560**

**Fax: +44 (0)1245 600030**

**Email: [sales@keison.co.uk](mailto:sales@keison.co.uk)**

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.