

RH9A Series

High resistance, high voltage decade resistance box with SP1 switch

Designed using the Cropico high-quality SP1 switch, combined with specially selected resistors, this range of high ohm resistance decades is ideal for the calibration of insulation test sets having a voltage rating up to 5kV.

Housed in a rugged carrying case and available in either 3, 6, or 9 decades, the RH9A series covers the range $1k\Omega$ to $1T\Omega$ and is equally at home in the laboratory workshop or field application.

A single decade unit is also available with 10 switched values from $1k\Omega$ to $1T\Omega$.

Each RH9A Series unit is supplied with high voltage test leads (1m in length) and calibration certificate.

Key Features

- 1, 3, 6 & 9 decades available
- Range $1k\Omega$ to $1T\Omega$
- Max voltage 5kV
- Accuracy $\pm 0.1\%$
- Portable case

Ideal For

- Calibration houses
- Laboratories/workshops



Technical Specifications

RH9A, RH9A-2 & RH9A-3 Specification

RH9A	RH9A-1	RH9A-2	RH9A-3	Decade	Accuracy @ Certified Voltage 1Kv Max	Typical Voltage Coeff	Max V/Step @ Certified Voltage 1Kv Max	Power Rating	Temp Coeff
✓		✓		10 x 1kΩ	±0.1%	<1ppm/V	30V	1W	±50 ppm/°C
✓		✓		10 x 10 Ω	±0.1%	<1ppm/V	100V	1W	±50 ppm/°C
✓		✓		10 x 100kΩ	±0.1%	<1ppm/V	300V	1W	±50 ppm/°C
✓		✓	✓	10 x 1MΩ	±0.1%	<1ppm/V	350V	1W	±50 ppm/°C
✓		✓	✓	10 x 10MΩ	±1%	1ppm/V	3,500V	1.5W	±100 ppm/°C
✓		✓	✓	10 x 100MΩ	±1%	1ppm/V	4,000V	1.5W	±100 ppm/°C
✓	✓		✓	10 x 1GΩ	±1%	1ppm/V	4,000V	3.5W	±100 ppm/°C
✓	✓		✓	10 x 10GΩ	±1%	1ppm/V	5,000V	3.5W	±250 ppm/°C
✓	✓		✓	10 x 100GΩ	±3%	25ppm/V	5,000V	1.3W	±2,000 ppm/°C

RH9A-5 Specification

Value	Accuracy @ Certified Voltage 1Kv Max	Typical Voltage Coeff	Max V/Step	Power Rating	Temp Coeff
1kΩ	±0.1%	<1ppm/V	30V	1W	±50 ppm/°C
10kΩ	±0.1%	<1ppm/V	100V	1W	±50 ppm/°C
100kΩ	±0.1%	<1ppm/V	300V	1W	±50 ppm/°C
1MΩ	±0.1%	<1ppm/V	350V	1W	±50 ppm/°C
10MΩ	±1%	1ppm/V	3,500V	1.5W	±100 ppm/°C
100MΩ	±1%	1ppm/V	4,000V	1.5W	±100 ppm/°C
1GΩ	±1%	1ppm/V	5,000V	3.5W	±100 ppm/°C
10GΩ	±1%	1ppm/V	5,000V	3.5W	±250 ppm/°C
100GΩ	±3%	25ppm/V	5,000V	1.3W	±2,000 ppm/°C
1TΩ	±3%	25ppm/V	5,000V	1.3W	±2000 ppm/°C

General Specifications

Dimensions

RH9A	460 x 380 x 160mm / 18 x 15 x 6.3" (w x h x d)
RH9A-1	460 x 380 x 160mm / 18 x 15 x 6.3" (w x h x d)
RH9A-2	460 x 380 x 160mm / 18 x 15 x 6.3" (w x h x d)
RH9A-3	460 x 380 x 160mm / 18 x 15 x 6.3" (w x h x d)
RH9A-5	220 x 110 x 90mm / 8.7 x 4.3 x 3.5" (w x h x d)

(All measurements approx)

Mass

RH9A	8.8kg / 20lbs
RH9A-1	7kg / 16lbs
RH9A-2	8kg / 18lbs
RH9A-3	8kg / 18lbs
RH9A-5	0.8kg / 2lbs

Services

1 year warranty (subject to product registration with Seaward.
Visit www.seaward.co.uk/register-product)

Service and calibration by Calibrationhouse.

Go to www.calibrationhouse.com for more information

Part Numbers

RH9A	930159
RH9A-1	930160
RH9A-2	930161
RH9A-3	930162
RH9A-5	930163



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.