

Dräger REGARD Relay display Control card

A control card to interface with the relay modules. The card has a local display, flexible relay logic and fault alarm.



D-15086-2009

The Dräger REGARD Relay display card and modules extend the output facilities for all addressed system input cards. A total of 256 relays per relay display card are achievable. All relays are fully configurable and can be configured to be voting, common or single alarms. The relay modules can be remotely located up to 1 km from the control card

FEATURES AND BENEFITS

- Voting alarm outputs
- Common alarm outputs
- Single alarm outputs
- Fully configurable
- Simple operation
- Continuous display
- Password protected
- Remote relay modules

TECHNICAL DATA

Control card	Local alphanumeric display Front panel push buttons Front panel LED's
Output	Fault relay
Inputs	RS 485 from remote relay modules Remote reset
Output Modules	Up to sixteen modules per relay card
Power Supply	24 V DC, 50 mA
Output Relays	Sixteen relays per relay module
Approvals	Designed to EMC EN50081-1 and 50082-2 ATEX II (2)G Acc. to Directive 94/9/EC
Safety Integrity Level	SIL2 certified by exida (IEC 61508)

ORDER INFORMATION

Dräger REGARD Relay display card	42 06 081
Dräger REGARD Relay module	42 06 432
Dräger REGARD Relay display card (DMT)	Upon request
Dräger REGARD Relay module (DMT)	Upon request
Dräger REGARD Relay card (ATEX)	42 06 719
Dräger REGARD Relay module (ATEX)	42 06 720



ST-327-2004



ST-336-2004

Dräger REGARD Relay display



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.