




CO DETECTION HEAD (GMS TYPE)

GMI PART NUMBER:	59375
GAS TO BE DETECTED:	CARBON MONOXIDE
RANGE:	0 – 100 Parts Per Million
Size:	38.5mm diameter.
Thread Connections:	20mm standard, others as required.
Material:	EN 316 Stainless Steel or 1802 Stainless Steel.
Supply Voltage:	24 Vdc ±10%.
Output Signal:	4 - 20 mA. Linear.
Typical Operating Life:	36 Months in air at STP.
Warranty Life	24 months
Connections:	Red – N.C. Yellow – Signal/supply. Blue – 0v. Green – Screen.
Temperature Range:	-10°C. to +50°C.
Pressure Range:	Atmospheric ±10%.
Relative Humidity:	15 to 90% non condensing.
Repeatability (typical):	+ / - 2% of Reading.
Zero Stability:	+ / - 1% F.S.D..
Response Time:	Typically 40 seconds to T90 Typically 20 seconds to T50.
CALIBRATION Frequency:	6 Months recommended
Certification:	 II 2 GD EEx d IIc T6.



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.