




FLAMMABLE DETECTION HEAD (Pellistor)

GMI PART NUMBER: 59290

GAS TO BE DETECTED:	FLAMMABLE For list, see calibration factors and consult manufacturer.
RANGE:	0 - 100% LEL
Size:	38.5mm diameter.
Thread Connections:	20mm standard, others as required.
Material:	EN 316 Stainless Steel or 1802 Stainless Steel.
Output Signal:	0.8 - 1.2mV / % LEL methane equivalent.
Operating Life:	1 - 5 years, depending on duty.
Warm-up Time:	5 minutes.
Temperature Range:	-25 Deg.C to +85 Deg.C as standard.
Pressure Range:	Ambient + / - 200 mbar.
Relative Humidity:	0 to +95% non condensing.
Span Accuracy:	+ / - 2% FSD.
Zero Stability:	+ / - 2% LEL.
Response Time:	Typically less than 10 seconds to T90.
Cross Sensitivity:	N/A
User Controls:	None
Certification:	 II 2 GD EEx d IIc T6.



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.