

GMI



Single Point Gas Alarm Gas Detection System



- /// Compact Stand Alone Unit
- /// Simple to Integrate into Larger Systems
- /// Relay Outputs
- /// User Selectable Alarm Settings
- /// Easy Installation
- /// One Man Calibration
- /// 4-20mA



GMI - PROTECTING ENVIRONMENTS . . . WORLDWIDE

The logo for GMI, consisting of the letters 'GMI' in a bold, white, sans-serif font on a black background.

Distributor

Gases

Flammable	0-100% LEL
Hydrogen Sulphide	0-100ppm
Carbon Monoxide	0-100ppm
	0-500ppm
	0-1000ppm
Oxygen	0-25%
Other Gases on Request	

CONTROL PANEL

Size

Height	230mm
Width	170mm
Depth	102mm

Weight

with battery	3.7kg
without battery	2.9kg

Terminals

Screw Types - Cable sizes up to 4mm

Degree of Protection

IP54

Power Supply

110-230v AC 50/60 Hz
24v DC

Display

1 Line 20 Digit LCD Display
(Backlit) 5 Status LED's

Operating Temperature Range

-10 Deg.C to +40 Deg.C

Relay Ratings

3 SPCO Relays rated 7A @ 250v AC ;
7A @ 30v DC

Humidity

5% - 95% RH Non Condensing

Alarm Settings

2 Levels adjustable
5% - 95% of range

Fault Detection

Open Circuit & Short Circuit
Line Fault Detection

OPTIONS

4-20mA Isolated Output
Panel Mounting Kit
Battery Back Up





Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.