

## Reliable pocket testers with high accuracy

Great for measuring conductivity, these two pocket-sized meters combine high precision with ease of use - making them excellent for on-the-spot testing on a budget.

### HI-98303 (DIST® 3)

Low range pocket EC meter

### HI-98304 (DIST® 4)

High range pocket EC meter


## Product Uses



Drinking water



Bottling plants



Circuit board  
manufacturing



Printing industry



Easy read digital  
display



Exposed  
temperature  
sensor for fast  
response time




HI-98303  
(DIST® 3)

HI-98304  
(DIST® 4)



Wipe-proof  
plastic casing



Includes  
protective cap,  
batteries and  
instructions

## Product Specifications

Product Code	HI-98303 (DiSt 3)	HI-98304 (DiSt 4)
Range	1999 $\mu$ S/cm	19.99 mS/cm
Resolution	1 $\mu$ S/cm	0.01 mS/cm
Accuracy	$\pm 2\%$ F.S	$\pm 2\%$ F.S
Calibration Solution	HI-70031	HI-70039 or HI-70030
Calibration	manual, 1 point	manual, 1 point
Probe	HI-73303	HI-73304
Temperature Compensation	automatic, 0 to 50°C	
Battery Type / Life	(4) 1.5V / approx. 200 hours of continuous use	
Environment	0 to 50°C; RH max 95%	
Dimensions	175 x 41 x 23 mm	
Weight	95 g	

## Main Benefits

- Automatic temperature compensation from 0 °C to +50 °C
- Graphite sensor for longer life and improved performance
- Manual single point calibration via trimmer



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



**UK Office**

**Keison Products,**

**P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.**

**Tel: +44 (0)330 088 0560**

**Fax: +44 (0)1245 808399**

**Email: [sales@keison.co.uk](mailto:sales@keison.co.uk)**

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.