

MODEL MD002

Monitored Driver Output Module



Features

- Four Monitored Driver Outputs
- Manual Abort and Release Input
- Microprocessor-based Electronics
- Setup, Setup Check & Inhibit Modes
- Power-on, Card & LED Test Modes

Benefits

- Flexible user configuration
- Simplifies system wiring
- Low component count, higher reliability
- Configuration easy to setup or change
- Functionality indicator, test(s) allows user to see all indicators

Description

The General Monitors MD002 is a monitored driver output module designed for four independent outputs requiring monitoring in their non-active state, such as extinguishing solenoids, beacons, horns, etc. Each driver output is independent and has circuitry to monitor short and open circuits in the field wiring.

The MD002 contains microprocessor-based electronics for advanced fault checking and operation. Selecting options is accomplished through software selections by using the Mode / Select button. The user selectable options are:

- Each driver in use or not in use
- Each driver's activation time delay (0-60 seconds)
- Each driver's manual abort enabled or disabled
- Active or passive Alarm outputs during Card Test
- Active or passive Fault outputs during Inhibit Mode
- Alarm inputs active Low or High
- Enabled or disabled password

Each module has RS-485 serial communications providing an interface with a General Monitors Model CC02A Modbus communications module. Fault and alarm status, as well as setup options can be configured via the CC02A module.

The MD002 is part of the Zero Two Series Gas and Flame Detection System which is a flexible solution for various combustible, toxic gas and fire detection applications. All of the Zero Two Series system cards are completely compatible and can be intermixed within the same rack if required. The Zero Two Series Rack includes options of 4, 8 or 16 channels and provides a bus of common terminals to each channel.

Applications

- Control Rooms
- Refineries
- Drilling Platforms and Rigs
- Gas and Oil Production Platforms
- Gas Collection and Distribution Facilities
- LPG / LNG Processing and Storage
- Chemical Plants
- Wastewater Treatment Facilities



MODEL MD002

System Specifications

Application:	Monitoring & activating devices such as extinguishing solenoids, beacons, horns, bells and HVAC damper controls
Front Panel Indicators:	ALARM - Alarm (each driver) READY - Normal Operation FAULT - Malfunction (each driver) SETUP - Set or check user options Digital Display - SETUP & FAULT codes
Test Features:	Power on - Electronic integrity Card - Functionality & Alarm Ramp LED - Integrity of LED's & Display
Modes:	Normal & Inhibit Outputs Manual Abort Manual Release
Standards:	Complies with applicable NFPA 72 standard
Electrical Classification:	General purpose, non-hazardous areas
Warranty:	Two Years
Approvals:	CSA, CE Marking, GOST

Environmental Specifications

Operating Temperature Range:	0°F to +150°F (-18°C to +66°C)
Storage Temperature Range:	-40°F to +150°F (-40°C to +66°C)
Operating Humidity Range:	5 to 100% RH, non-condensing
EMC Susceptibility:	Conforms to EN50081-1, EN50082-1 10V/m max.

Electrical Specifications

Input Power:	20 to 35 VDC
Driver Inputs:	2.0 mA max. @ +35 VDC, sinking
Output Drivers:	4 outputs at 1.2 Amps @ +24 VDC each
Monitoring Resistance:	20 to 200 Ohms
Open Collector Rating:	100 mA @ 30 VDC maximum Fault, Fault-Unaccept, Inhibit
RFI Susceptibility:	Complies with BS 6667 Part 3/IEC 801-3. Severity level 3

Mechanical Specifications

Length:	9.9" (251mm)
Height:	6.8" (173mm)
Width:	1.0" (25mm)
Weight:	11.2 oz. (318 grams)
Standard Configuration:	MD002-1-1-00-1-1-1-0-1

Specifications subject to change without notice.

Represented by:



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.