



3M™ Protecta® Rebel™ Self-Retracting Lifeline

Total compliance, absolute confidence.

Rebel SRLs are available with a heavy duty aluminium or a durable lightweight thermoplastic housing, providing an economical fall protection solution without compromising on performance or safety. Integrated ergonomic carrying handle and top swivel connector ensure easy transport and installation. Built-in fall indicator hook allows visual yearly inspection. Rebel Cable blocks meets the latest CE sharp edge certification when used with an extension sling.

Applications



Anchor Swivel

Allows the block to align with lifeline and avoid any torsion of the cable when the user is working.

Choice of Housing (Thermoplastic or Aluminium)

Durable thermoplastic for lightweight or aluminium for ultimate ruggedized housing allows for job site flexibility.

Galvanized or Stainless Steel 5 mm Cable or High-strength polyester webbing

Larger cable diameter for added strength and safety.

Side Cable Exit

Allows best alignment of the cable and minimises cable guide wear.

140 kg Weight Capacity

High capacity allows for use by most users and tools ensuring the highest level of safety.

Ergonomic Cable Bumper

Allows the block to align with lifeline and avoid any torsion of the cable when the user is working.

Ergonomic Carrying Handle

Allows easier transportation of the block.



3M™ Protecta® Rebel™ Cable Self-Retracting Lifelines - 4.5 m



CE EN360

	←→	⚙	⚙	⚙	⚙	kg
3590024	4.5 m	⚙	⊕	⊕	⊕	2.80

Rebel Cable SRL - 6 - 15 m



Best Seller
3590521
& 3590570

CE EN360

	←→	⚙	⚙	⚙	⚙	kg
3590520	6 m	⚙	⊕	⊕	⊕	5.30
3590521	10 m	⚙	⊕	⊕	⊕	5.60
3590522	10 m	⚙	⊕	⊕	⊕	5.60
3590570	15 m	⚙	⊕	⊕	⊕	7.50
3590571	15 m	⚙	⊕	⊕	⊕	7.50

Rebel Cable SRL - 20 - 30 m



Best Seller
3590610

CE EN360

	←→	⚙	⚙	⚙	⚙	kg
3590610	20 m	⚙	⊕	⊕	⊕	10.00
3590611	20 m	⚙	⊕	⊕	⊕	10.00
3590650	25 m	⚙	⊕	⊕	⊕	13.00
3590651	25 m	⚙	⊕	⊕	⊕	13.00
3590690	30 m	⚙	⊕	⊕	⊕	13.40
3590691	30 m	⚙	⊕	⊕	⊕	13.40

3M™ Protecta® Rebel™ Horizontal Use Extension Sling

CE EN360

	kg
3500050	2.00

Mandatory for Rebel cable blocks to be compliant with the latest horizontal sharp edge requirements VG 11.

3M™ Protecta® Rebel™ Cable SRL Cover



Best Seller
3590010

	Description	kg
3590010	For 6 m, 10 m Rebel models	0.20
3590011	For 15 m Rebel models	0.20
3590012	For 20 m, 25 m, 30 m Rebel models	0.28

3M™ Protecta® Rebel™ Web Self-Retracting Lifelines - 2 m



Best Seller
3100418

CE EN360

	←→	⚙	⚙	⚙	⚙	⚙	kg
3100418	1.9 m	⚙	17 mm	⚙	⊕	⊕	1.00
3100419	2 m	⚙	57 mm	⚙	⊕	⊕	1.20
3100420	2 m	⚙	17 mm	⚙	⊕	⊕	1.20
3100421	2 m	⚙	57 mm	⚙	⊕	⊕	1.40
3100422	2.1 m	■	57 mm	⚙	⊕	⊕	2.60

Rebel Cable Leading Edge SRL



CE EN360

	←→	⚙	⚙	⚙	⚙	⚙	kg
3590542	6 m	⊕	5.6 mm	⚙	⊕	⊕	5.60
3590545	12 m	⊕	5.6 mm	⚙	⊕	⊕	8.50

The only SRL that complies to extreme sharp edge (VG11.054, type B, 0 mm radius). Users are now able to tie-off at foot level with the 6 m Leading Edge Rebel without requiring to connect the sharp edge extension sling. This built-in sharp edge product was put through extensive sharp edge testing to ensure absolute protection against sharp, abrasive and leading edges found at construction sites.

Rebel Cable Retrieval SRL



CE EN360

EN 1496

	←→	⚙	⚙	⚙	⚙	⚙	kg
3591002	15 m	⊕	5 mm	⚙	⊕	⊕	11.90
3591003	15 m	⊕	5 mm	⚙	⊕	⊕	11.90

These Retrieval models incorporate fall arrest and a built-in emergency retrieval winch for rescue, making them a versatile solution for many job sites.

- 15 m SRL with rescue winch
- Brackets available for easy tripod integration
- Designed for confined space applications

3590498 - Bracket for AM100 Protecta tripod
3590499 - Bracket for DBI-SALA® tripods KM1PT7 and KM1PT9

Rebel Web SRL - 3 m



CE EN360

	←→	⚙	⚙	⚙	⚙	kg
3100423	3 m	⚙	⊕	⊕	⊕	1.40

Best Seller
3100423

Rebel Web SRL - 6 m



CE EN360

	←→	⚙	⚙	⚙	⚙	kg
3100437	6 m	⚙	⊕	⊕	⊕	2.20

Best Seller
3100437