

AutoRAE Lite Station

AutoRAE Lite automated bump and calibration station for QRAE II



The AutoRAE Lite high-speed, low-operating-cost bump test and calibration station stores data in a text file that can be opened by any spreadsheet software or text editor. In addition, the AutoRAE Lite operates on a low-pressure system with a built-in pump.

12-second bump test

2-minute calibration

Configures gas monitor

Full documentation storage

Portable with battery option

**Demand-flow system
eliminates accidental leaks**

Key Features

- Fully automated bump and calibration
- Bump test in 12 seconds
- Full calibration in 2 minutes
- Tamper-proof data files
- Optional battery operation
- Configures monitor
- "No gas flow" alarm
- Demand-flow system



*Calibrating QRAE II
with AutoRAE Lite
Bump Test and
Calibration Station*



AutoRAE Lite Station

Specifications

Detector Specifications*

Certifications	CE
Sensor	Light and sound sensors
Data Storage	Text files (format can be opened by any spreadsheet software or text editor), saved daily for: 1. Bump tests 2. Calibrations 3. Alarms Tamper-proof
Bump Test Time	12 seconds
Bump Test Gas Usage	70 cm ³
Calibration Time	2 minutes
Calibration Gas Usage	300 cm ³
Pneumatic System	Demand-flow regulator Built-in pump "No gas flow" alarm
Power Supply	Universal power cord or battery pack
Operating Temperature	+14° F to +122° F (-10° C to +50° C)
Humidity	10% to 90% relative humidity, non-condensing
Dimensions	15" L x 12.5" W x 6.5" H (38cm x 32cm x 17cm)
Weight	8.56 lbs (3.9 kg)

*Specifications are subject to change

AutoRAE Lite includes:

- AutoRAE Lite as specified
- USB cable for PC setup
- Universal power supply
- Demand-flow regulator
- SD memory card, minimum 512Mb
- Quick-start guide
- Inlet filter
- Diffusion adapter
- CD includes:
 - Operation manual
 - Drivers
 - Utility software

Ordering Information

Part Numbers

AutoRAE Lite

Bump Test and Calibration Station for QRAE II	T01-0001-000
Bump Test and Calibration Station for ToxiRAE 3	T01-0100-000





Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.