

# PROPAK-I

*HIGH PERFORMANCE, RUGGED DEPENDABILITY, TRUSTED TECHNOLOGY*



The ProPak-i has been designed for use as a fire fighting set in the Industrial, Professional Fire Fighting or Oil & Gas markets.

The entire ProPak range has been approved to EN137:2006 Type 2, incorporating the stringent Full Flame Engulfment Test, and to the 9th amendment of the MED meaning that it has the latest approval for the Marine industry.

## **PRODUCT HIGHLIGHTS**

---

- EN137:2006 Type 2 MED Approved Breathing Apparatus
- Compliance set for Industrial Professional Fire Fighting or Oil & Gas markets
- Rigid backframe construction
- Easily removable pneumatics
- Simple to service and maintain

# PROPAK-I

## SELF CONTAINED BREATHING APPARATUS



### MAJOR COMPONENTS

Compact positive pressure demand valve featuring servo-assisted, tilting diaphragm mechanism with low inspiratory resistance and responsive dynamic performance, automatic first breath actuation and hands free bypass facility

### REDUCING VALVE

First stage pressure reducing valve featuring non-adjustable, spring loaded piston mechanism and outlet supply protected by pressure relief valve

### HOSES

Stainless steel swivel hose fittings  
 Medium pressure hose  
 High pressure hose  
 Medium working pressure 16 bar  
 Minimum burst pressure 80 bar  
 Maximum working pressure 450 bar  
 Minimum burst pressure 800 bar

### PRESSURE INDICATOR & WARNING WHISTLE

Bourdon tube type dial indicator  
 Heat and Impact resistant polycarbonate lens

### COMMUNICATIONS

The Sabrecom2 is a radio communication interface designed for use with Scott Safety's range of positive pressure full facemasks. Fully integrated and ready to use the Sabrecom 2 is approved to EN136 class 3, meeting the stringent flame and radiant heat test requirements.

### OPTIONS

The Scott Safety ProPak-i can be specified in many configurations including Split Demand Valve Coupling (SDC), Y-Piece (Y2C) and attachments for Airline, which can be used for Rescue Second Man and Decontamination.

Product Specifications		
<b>Weight</b>		
Single Configuration (less cylinder)		2.9kg
Single Configuration and facemask (less cylinder)		3.5kg
<b>Dimensions</b>		
Length		630mm
Width		285mm
Depth (with a 6 litre 200 bar cylinder)		220mm
Ordering Information		
Part Number	Description	Application
ProPak-I	EN137 Approved, Type 2	Industrial/Oil & Gas Fire Fighting





Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



**UK Office**

**Keison Products,**

**P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.**

**Tel: +44 (0)330 088 0560**

**Fax: +44 (0)1245 808399**

**Email: [sales@keison.co.uk](mailto:sales@keison.co.uk)**

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.