

SV 38V

Whole-Body Vibration Accelerometer

The SV38V accelerometer is dedicated for whole-body vibration measurements with the SV 106 human vibration analyser. The accelerometer has a built-in memory (TEDS) containing information about the sensitivity that is automatically transferred to the SV 106 instrument. In accordance with ISO 2631-1 seat accelerometers such as SV 38V are placed on the operator's seat either on the seat-rest.



Technical Specifications

Performance:

Number of Axes	3
Sensitivity ($\pm 5\%$)	50 mV/(ms ⁻²) at 15.915 Hz
Measurement Range	0.01 ms ⁻² RMS \div 50 ms ⁻² PEAK
Frequency Response (by design guideline, ± 3 dB)	0.1 Hz \div 100 Hz
Resonant Frequency	5.5 kHz (MEMS transducer)
Electrical Noise	< 0.005 ms ⁻² RMS, HP1 weighting

Electrical:

Supply Current	< 5.0 mA
Supply Voltage	5.2 V \div 16 V
Bias Voltage	2.5 V \pm 0.05 V
Output Impedance	51 Ohms
Charge / Discharge Time Constant (start-up time)	30 sec. typ.
TEDS Memory	installed (power supply pin)

Environmental Conditions:

Maximum Vibration	100 000 ms ⁻² shock survival for MEMS sensor
Temperature Coefficient	< \pm 0.01 %/ $^{\circ}$ C
Temperature	from -10 $^{\circ}$ C to +50 $^{\circ}$ C
Humidity	up to 90 % RH, non-condensed

Physical:

Sensing Element	MEMS
Cable	integrated 1.4 meters
Connector	LEMO 5-pin plug (SV 106 compatible)
Dimensions	236 mm diameter; thickness from 3.6 mm to 12 mm
Weight	550 grams (including cable and rubber cushion)

Accessories:

SA 38 (optional)	Calibration adapter
------------------	---------------------

The policy of our company is to continually innovate and develop our products. Therefore, we reserve the right to change the specifications without prior notice.